



FOOD PRESERVATION AND SOUS-

SOUS-VIDE COOKERS



Immersion Circulator SmartVide 8

MAX. CAPACITY: 56 LT./14 GAL.

Commercial high-precision sous-vide cooker. Reliable, user-friendly, portable. Interchangeable between °C and °F. 4 user-friendly control buttons.

Portable precision cooker with stirrer for up to 56 lt. / 14 gal. containers. Designed for chefs, developed with chefs.

- \cdot The thick stainless steel, robust construction guarantees commercial performance.
- Smart Vide guarantees cooking at a precisely controlled temperature while preserving the quality of the product, enhancing flavour and texture. Equipped with a highly precise temperature control system to obtain extremely consistent results. An optional core probe allows getting an even more precise control.
- · Allows cooking food in their own juice and using this juice immediately after cooking to enhance flavours.
- · Marinates and macerates an ingredient in half the time.
- \cdot Infuses and flavours oil, fat or other products applying the controlled temperature technique.
- · Increases profits due to lack of product shrink.
- Requires very little hands-on time, allowing the Chef to do other tasks while the product is being cooked. Just program temperature and time, Smart Vide will do the rest. 4 buttons and a full-colour TFT display that offers all the information at a glance makes operation a chil's play.
- · SmartVide8 is portable: thanks to their thick, stainless steel, ergonomic handle, SmartVide8 can be taken from a container to another easily. Additionally, the bag supplied with the circulator allows easy transport wherever the Chef goes.





2006/95/CE, 89/336/CE

EN 61010: 1 , EN 51010:2010 , EN 61326





FOOD PRESERVATION AND SOUS-**VIDE**

SOUS-VIDE COOKERS

Immersion Circulator SmartVide 8



TECHNICAL SPECIFICATIONS

Temperature

Display precision: 0.01 °C Range: 5 °C - 95 °C

Permissible ambient temperature: 5 °C - 40 °C

Resolution: 1'

Cycle duration: 1 ' - 99 h

General features

Bluetooth connectivity: n

HACCP-ready: n

Maximum recipient capacity: 56 Lt

Total loading: 2000 W
Submergible part dimensions: 117 mm x 110 mm x 147 mm
External dimensions (WxDxH): 124 mm x 140 mm x 360

Net weight: 4.1 Kg

DEFAULT EQUIPMENT

- Stainless steel handle and panel.
- Transport bag.

OPTIONAL EQUIPMENT

- Core probe.
- Insulated tank. Lid for insulated tank.