



Product Code: HR120 13-122

Space Saver Refrigerated Undercounter Cabinet

---



## Features & Benefits

---

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate in ambient up to 40°C
- GN1/1 Undercounter storage on a small footprint

| External Finish                      |          |
|--------------------------------------|----------|
| 304 s/s                              | Standard |
| Worktop                              | Standard |
| Base Fittings                        |          |
| Castors - Rear Fixed                 | Standard |
| Levelling Bolts                      | Standard |
| Electrical, Service & Ecodesign Data |          |
| 230/50/1                             | Standard |
| Fuse Required                        | 13       |
| Global Warming Potential             | 1430     |
| Energy Efficiency Index              | 22.34    |
| Refrigerant Charge                   | 0.160    |

| Internal Finish       |          |
|-----------------------|----------|
| aluminium             | Standard |
| Doors                 |          |
| Solid                 | Standard |
| Specification         |          |
| Dimensions (Width)    | 440      |
| Dimensions (Height)   | 895      |
| Dimensions (Depth)    | 745      |
| Weight (Unpacked, kg) | 69       |
| Weight (Packed, kg)   | 77.02    |
| Gross Volume          | 120      |
| Noise DbA @ 1M        | TBC      |

| Shelving                      |          |
|-------------------------------|----------|
| GN1/1 Shelf                   | Option   |
| Refrigeration                 |          |
| R134a - Industry Standard     | Standard |
| Integral Refrigeration System | Standard |

## Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for airflow, ensure that 25mm clearance is allowed above the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet



**Application**

This appliance is intended for use in ambient temperatures up to 40°C

**Safety**

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

**Recycling**

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care