Electric Oven Range 600mm wide

OE8010

- Heavy-duty cast iron 2.6kW hotplates deliver fast responsive heat
- Choice of square or round hotplates
- Fully pressed sealed hob for easy cleaning
- 4kW, fan assisted oven
- Large capacity oven 3 x GN1/1
- Double insulated doors and side panels for safe operation, efficiency and economy





Hob Top Features

- 4 x heavy duty cast iron hot plates with 2.6kW elements
- Round plates on OE8016 and square plates on OE8008
- Simmerstat control (six settings)
- Fully pressed hob top for easy cleaning

Oven features

- 4kW heating element
- Precise thermostatic control from 50 °C to 250 °C
- Fan assisted oven
- Power ON indicator light (green)
- Oven has reached desired temperature indicator light (amber)
- 180° side hinged doors
- Oven capacity 3 x GN1/1
- Heavy-duty easy remove wire chrome rack supports
- 5 position racking with anti tilt guards and safety stops

Cleaning and Servicing

- Fully sealed hob top for easy cleaning
- Easy clean stainless steel external finish
- Heavy-duty easy remove wire chrome rack supports
- Stainless steel oven lining with removable side and base liner

Overall construction

- Permanent laser etched markings on fascia and knobs
- Fully framed 1.2mm steel chassis
- 1.2 mm stainless steel base panel
- 0.8 mm stainless steel side panels
- Castors as standard
- Sits flush to the wall, recess for service

Hob top construction

• 1.2 mm stainless steel welded bull nose and hob surround

Oven construction

- 0.8 mm stainless steel outer door skin
- Reinforced door seal
- Double insulated doors, side and back panels
- Stainless steel oven liner

Inclusive Accessories


• 3 chrome plated shelves






Technical Data

	OE8010
Width (mm)	600
Depth (mm)	800
Overall height (mm)	925
Hob height (mm)	900
Usable oven capacity h x w x d (mm)	419 x 480 x 510
Oven shelf size w x d (mm)	480 x 510
Hob	4 square hotplates
Fan	Single fan
Hob rating per hotplate (kW)	2.6
Oven rating (kW)	4.0
Total electrical power rating (kW)	14.4
Electrical supply 3N~+E 400V 50-60Hz Current Rating (Amps)	L1 = 17.4 L2 = 22.6 L3 = 22.6
Net weight (kg)	109
Packed weight (kg)	121
Shipping volume (m3)	0.9
IPX Protection	IPX4













WK Sales e-mail: sales@lincat.co.uk

■ International Sales Tel: +44 1522 503250
■ International Sales e-mail: export@lincat.co.uk



