

E3101 OTC SIX HOTPLATE RANGE





MODELS and ACCESSORIES

E3101OTC 6HP - Six hotplate range - fan-assisted oven

- Fully integrated extended flue
- Splashplate and plateshelf
- Oven shelf
- Factory fitted, adjustable castors
- Fixed installation kit
- Suiting kit

KEY FEATURES

- Six fast-acting circular hotplates
 - Reduces heat up times, energy efficient
- Full width, removable drip tray
 - Retains spillages and keeps unit clean
- Vitreous enamelled oven chamber
 - Easy to clean and to keep clean
- Wide oven temperature range of 100 250°C
 - Ideal to prepare a wide variety of food
- Glass panels in oven doors
 - Monitor cooking without losing valuable heat
- Ovens have twin doors with individual catches
 - Retains heat within the oven chamber
- Oven has 5 shelf positions to allow 2 shelf cooking
 - Versatile, ideal for a wide range of menu items
- Low profile door handles
 - Reduces intrusion into work space
- · Laser-etched control icons
 - Permanent, indelible markings

INSTALLATION NOTES

Adequate ventilation must be provided to supply sufficient fresh air and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.






DOMINATORPLUS

E3101 OTC SIX HOTPLATE RANGE

MODEL DIMENSIONS (in mm)



SPECIFICATION DETAILS

F3101	OTC	CHD
F.3 1 U I	UIU	nnr

Electrical rating (kW) 20.2

Electrical supply voltage 400V 3N~ / 230V~

Minimum electrical supply 230V~ (amps) 100 Minimum electrical supply 400V 3N~ (amps) 32

Electrical current split (amps) L1: 24 / L2: 24 / L3: 28.3

Hotplate rating (kW) 6 x 2.3

Total oven element rating (kW) 6.4 (2 x 3.2)

Oven dimensions (w x d x h - mm) 700 x 535 x 430

Oven shelf (w x d - mm) 700 x 535

Gastronorm compatibility 2/1
Weight (kg) 157
Packed weight (kg) 175

