



Turbo Liquidiser TRX-21

1-SPEED TURBO-MIXER

Turbo-blender designed to work in up to 800 litre / 130 gal. bowls.

- Fully manufactured in stainless steel 18/10.
- For mixing and liquidising directly in the pot or pan for making consommés, soups, omelettes, mayonnaise, etc.
- Designed for large yields and for frequent use and cleaning, ideal for kitchens with a large production and the food industry.
- 1-speed model.
- Ease of use: can be moved in several directions, adjustable height, fitted on a trolley with 4 non-slip rubber wheels, 2 of them with brakes.
- Arm: 600 mm long for blending in any type of cooking pot, whether round or rectangular, equally effective throughout the whole pot.
- Balanced liquidiser arm: stops the arm falling or tipping back when not locked.
- Arm securing lever: allows you to lock the blender with one hand while holding the trolley with the other.
- Watertight, tilted control panel: easy access even during use.
- Control panel located on the trolley, making the arm more agile, with better mobility.
- Control panel with built-in timer: you can leave the machine running for up to 60 minutes without the need for user involvement.
- Wiring incorporated into the trolley tubes: The work area is free of cables, so as not to hinder the movement of the blender arm.
- Supports for storing the power supply cable: prevents the cable getting tangled and inconveniencing other users.
- The turbine, disc and grille are very easy to remove for cleaning: no tools needed.
- The turbine, guard, disc and attachment can be cleaned in dishwashers.
- For use with 3 easily interchangeable attachments, which meet the needs of all users and ingredients.
- 21D for fibrous ingredients
- Standard 30D multi-use attachment
- 42D attachment for very fine blending
- Safety microswitch to control the work position: prevents the turbine working if the arm is too high or low.
- Safety guard on the liquidiser head and safety device that cuts out the power supply.





Turbo Liquidiser TRX-21



TECHNICAL SPECIFICATIONS

Maximum recipient capacity: 800 l

Liquidising arm length: 600 mm

Total loading: 2200 W

Speed (in liquid): 1500 rpm

External dimensions (WxDxH)

·Width: 568 mm

·Depth: 1643 mm (963 mm)

·Height: 1219 mm (1651 mm)

Net weight: 96 Kg

Noise level (1m.): <70 dB(A)

Background noise: 32 dB(A)

DEFAULT EQUIPMENT

- Trolley, motor and arm (without attachments).

OPTIONAL EQUIPMENT

Attachments:

- 21D for fibrous ingredients
- Standard 30D attachment for general use
- 42D attachment for very fine blending