



Product Code: EP1440LU

EcoPro G2 1350 Litre Upright Undermount Freezer Cabinet

---



## Features & Benefits

---

- Sleek, modern aesthetics, robust construction and market leading capacity. 'Smartphone style' fuzzy logic II touch sensitive control panel with high visibility temperature display
- Low energy refrigerant system with reduced running costs
- Improved internal fittings for easy cleaning
- Foster Circular II air distribution system maximises efficient operation even when shelves are fully loaded
- Operates efficiently in ambients up to 43°C
- Provides an alternative format for high ambients as it takes cooler air from floor level
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

External Finish	
s/steel ext, 304 s/s door	Standard
304 s/s	Option
304 S/S back for island sitting	Option

Base Fittings	
Castors 80mm	Standard
Legs 150mm	Option
Levelling Bolts	Standard

Electrical, Service & Ecodesign Data	
230/50/1	Standard
220/60/1 Electrical Supply	Option
Fuse Required	13
Global Warming Potential	3922
Energy Efficiency Index	99.29
Refrigerant Charge	0.570

Internal Finish	
aluminium	Standard
304 s/s	Option

Doors	
Solid	Standard

Product Extras	
Helicoil Mains Lead	Option

Shelving	
Additional S/S Trayslides	Option
Additional GN2/1 Shelf	Option

Refrigeration	
R404a - Industry Standard	Standard
Integral Refrigeration System	Standard
Less Condensing Unit	Option
Remote Refrigeration System	Option

Specification	
Dimensions (Width)	1440
Dimensions (Height)	1980
Dimensions (Depth)	865
Weight (Unpacked, kg)	182.5
Weight (Packed, kg)	199.1
Gross Volume	1350
Noise DbA @ 1M	TBC

## Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



**Application**

This appliance is intended for use in ambient temperatures up to 40°C

**Safety**

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

**Recycling**

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care