





Dual Fuel Range 600mm wide

OD8006

- 7.5kW dual concentric burners for focused heat distribution from a fast boil to a low simmer
- Individual heavy-duty single cast iron supports, built to withstand the rigours of the busiest kitchen
- Low flue to allow use of the complete hob top
- 4kW, fan assisted oven
- Large capacity oven 3 x GN1/1
- Double insulated doors and side panels for safe operation, efficiency and economy



Hob Top Features

- 4 x 7.5kW dual-concentric burners
- Individual heavy-duty single cast iron pan supports with extended pan support fingers
- Flame failure protection
- Stainless steel spill trays
- Low flue to allow complete use of hob top

Oven features

- 4kW heating element
- Precise thermostatic control from 50 °C to 250 °C
- Fan assisted oven
- Power ON indicator light (green)
- Oven has reached desired temperature indicator light (amber)
- 180° side hinged doors
- Oven capacity 3 x GN1/1
- Heavy-duty easy remove wire chrome rack supports
- 5 position racking with anti tilt guards and safety stops

Cleaning and Servicing

- Easy clean stainless steel external finish
- Removable stainless steel spill trays
- Heavy-duty easy remove wire chrome rack supports
- Stainless steel oven lining with removable base liner
- Access to all parts from the front and top of unit

Overall construction

- Permanent laser etched markings on fascia and knobs
- Fully framed 1.2mm steel chassis
- 1.2 mm stainless steel base panel
- 0.8 mm stainless steel side panels
- Castors as standard
- Sits flush to the wall, recess for services

Hob top construction

• 1.2 mm stainless steel welded bull nose and hob surround

Oven construction

- 0.8 mm stainless steel outer door skin
- Reinforced door seal
- Double insulated doors and side panels
- Stainless steel oven liner

Inclusive Accessories

• 3 chrome plated shelves

Available Options

- Adjustable legs
- /N Natural or /P propane gas


Available Accessories


OA8901 splashback/shelf




Technical Data

	OD8006
Width (mm)	600
Depth (mm)	800
Overall height (mm)	910
Hob height (mm)	900
Usable oven capacity H x W x D (mm)	419 x 480 x 510
Oven shelf size W x D (mm)	480 x 510
Hob	4 open burners
Heat input per hob burner (kW)	7.5 natural, 6.7 propane
Oven rating (kW)	4.0
Total heat input at full rate (kW)	30 natural, 26.8 propane
Total heat input at full rate (Btu per hour)	102,364 natural, 91,445 propane
Gas consumption at full rate Natural (m3 h-1)	2.86
Gas consumption at full rate Propane (kg h-1)	1.92
Gas pressure	20 natural, 37 propane
Gas connection (BSP)	1/2"
Oven rating (kW)	4
Total electrical power rating (kW)	4
Electrical supply 1N~+E 230V 50-60Hz Current Rating (Amps)	17.8
Electrical supply 3N~+E 400V 50-60Hz Current Rating (Amps)	L1 = 8.8 L2 = 8.7 L3 =
Net weight (kg)	119
Packed weight (kg)	131
Shipping volume (m3)	0.9











© UK General Tel: 01522 875555

Fax: +44 (0)1522 875530

WK Sales e-mail: sales@lincat.co.uk

■ International Sales Tel: +44 1522 503250
■ International Sales e-mail: export@lincat.co.uk







