



British Manufacturing
since 1957



The Professionals Choice

CTSP11H/6

SureFlow Plus Counter Top with built in Filtration (High Level Tap)



FULL SPECIFICATION



SureFlow Plus Counter Top Automatic Fill Water Boiler with built in Filtration (High Level Tap)

| | |
|---|---|
| Type | Countertop - <i>Premium Range</i> |
| Country of Design & Manufacture | UK |
| <u>CAPACITY, WEIGHTS & DIMENSIONS:</u> | |
| Capacity (Litres) | 10 |
| Unit dimensions (W x D x H) mm | 260 x 555 x 705 (depth includes drip-tray) |
| Packed dimensions (W x D x H) mm | 360 x 595 x 830 |
| Tap clearance mm | 304mm (extra clearance for tall jugs, teapots & cafetieres) |
| Product weight - empty (kg) | 16.8 |
| Product weight – full (kg) | 31.5 |
| Packed weight (kg) | 19.6 |
| <u>CONSTRUCTION:</u> | |
| Outer fabrication (body) construction | 304 grade Stainless Steel (Superbrush polish) |
| Tank construction | 304 & 316 grade Stainless Steel |
| Tank wall thickness | 0.9mm |
| Drip-tray | 304 grade Stainless Steel – (Mirror polish) |
| <u>ELECTRICAL:</u> | |
| Power rating (kW) | 6 |
| Voltage supply | 230 V (50-60Hz) |
| Electrical supply | Single-phase, N & E (25A) |
| Electrical Installation | Wire to 30A single-phase supply via an isolation switch |
| Fitted cable length (m) | 1.6m (3-core HR @ 2.5 ² mm) |
| <u>PLUMBING:</u> | |
| Water inlet connection: | 3/4" BSP |
| Food quality, flexible mains water hose | 1.6 metre long, (3/4"BSP) |
| Mains water pressure range | 2 – 7 bar (28psi – 100psi) |
| Overflow/waste connection: | Choice of front (via drip-tray) or rear (1/2"BSP – 15mm) |
| <u>PERFORMANCE:</u> | |
| Water temperature delivered | 96°C (default) – can be adjusted if required |
| Heat up time to working temperature | 16 mins (full tank capacity) |
| Output per hour (@ default temperature setting) | 57 Litres (higher output/hour if set @ lower temperature) |
| Rapid draw-off | 11 Litres |
| Recovery per minute | 1 Litre |
| Stand-by power loss (idle mode) | 0.084 kW/h |
| <u>FILTRATION:</u> | |
| Multi-Filter (taste & odour, sediment & reduces lime-scale) | Yes |
| Filter Benefits | Latest triple-action; removes sediment & impurities such as chlorine and reduces limescale build-up |
| Max recommended filter capacity | 13,500 (or 6 months) |
| Mechanical sediment filtration | 3 micron |
| Filter counter programmable | Yes (between 2000 & 19,500 litres) |
| <u>OTHER FEATURES:</u> | |
| 7 day programmable timer | Yes |
| Energy saving ECO mode | Yes |
| Tank-baffle plates – unique design aids heat recovery & reduces steam emissions to atmosphere | Yes |
| Early warning lime-scale diagnostics (via LCD) | Yes |
| Dual safety protection | Yes - Over-boil & boil-dry protection |
| <u>STANDARDS & APPROVALS:</u> | |
| WRAS approved | Yes |
| EMC Tested and Certified (EN 55014 & EN 61000) | Yes |
| Electrical Safety Tested and Certified to BS standard | Yes (BS EN 60335-1 & 2) |
| <u>WARRANTY & AFTER-SALES:</u> | |
| Guarantee | 2 Year parts & labour |
| Spare parts, filters & accessories | Same day despatch (if ordered before 3pm) |

Instanta Limited

T: 01704 501114 F: 01704 501115 E: sales@instanta.com



Certificate Numbers: FM01234 & EM01234