





300

COUNTERTOP INDUCTION HOB STAINLESS STEEL



Two cooking zones (1.8kW and 1.2kW) which can be set at different temperatures for greater cooking flexibility.

Hardwearing Schott glass surface built to withstand the impact of large pans and any spills can be easily wiped away in seconds.

Touch controls

that are not only simple to operate but also easy to clean, maintaining high levels of hygiene.

0-99 minute timer

for foods that need to be cooked slowly or kept simmering at low heat – ideal for soups and sauces.

Non-slip feet

for extra safety on the kitchen counter.

UK 3 pin plug

just plug in and get started.

SKU CODE: PRODUCT CODE:

DESCRIPTION:

444440541 CTIN01

Countertop Induction Hob Stainless Steel

Glen Dimplex Professional Appliances Stoney Lane, Prescot, Merseyside, L35 2XW



FULL SPECIFICATION – CTIN01 Countertop Induction Hob Stainless Steel

A CARLENCE PAR

SKU code44440541GDPA codeCTIN01EAN code5052263005419Unit external width (mm)400Unit external depth (mm)600Unit external height (mm)275Packed width (mm)465Packed height (mm)680Packed weight (kg)12Packed weight (kg)12Packed weight (kg)14.5Variable ControlYesEasy clean stainless stel constructionYesPower on indicator lightNon-slip fet for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Gilling surface area (mm) (WxD)-Plate temperature range60°C to 240°CTemperature range-Plate temperature range-Power rating on each otoplete (kW)1x1.8/1x1.2Drainage tap diameter-Touch controlYesEven heat distributionYesPower rating on each otoplete (kWD)-Tank dimension (mm) (WxDH)-Tank dimension (mm) (WxDH)-Tank dimension (mm) (WxDH)-Tank dimension (mm) (WxDH)-Safety cout-Hinged element<		
EAN code5052263005419Unit external width (mm)400Unit external depth (mm)600Unit external height (mm)275Packed width (mm)465Packed wight (mm)415Product weight (kg)12Packed weight (kg)12Packed weight (kg)14.5Variable ControlYesEasy clean stainless steel constructionYesPower on indicator light-Non-slip fer for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UX 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Contents-Grilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CGrilling surface area (mm) (WxD)-Power rating height-Touch controlYesPlate temperature range-Material-Touch controlYesPlate temperature range-Material-Touch controlYesPlate temperature range-Material-Heat up indicator lightTouch controlYesPower rating on each hotplate (kW)11.8/1x.1.2Drainage tap diameter	SKU code	44440541
Unit external width (mm)400Unit external height (mm)600Packed width (mm)465Packed depth (mm)680Packed height (mm)415Product weight (kg)12Packed width (mm)415Variable ControlYesEasy clean stainless stel constructionYesPower on indicator light-Non-slip feet for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UX 3 pin plugYesFitted cable height (mn)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Grilling surface area (mm) (WXD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesPlate temperature range-Heat up indicator light-Touch controlYesPlate temperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower at distributionYesPower at distributionYesPater distributionYesHeat up indicator light-Tank capacity (L)-Tank capacity (L)-Tank capacity (L)-<	GDPA code	CTIN01
Unit external height (mm)600Unit external height (mm)275Packed vidth (mm)465Packed deight (mm)680Packed veight (kg)12Packed veight (kg)12.Packed veight (kg)14.5Variable ControlYesPower on indicator light-Non-slip fect for safetyYesPower rating (kW)3.1Voltage supply (V)220/240Ukt 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Contot-Thermal protection-Thermal protection-Master au (mins)InstantGrilling surface area (mm) (WxD)-Filted collection drawer-Power taing ing on each oblight-Touch controlYesFilted collection drawer-Contouth operation-Contents-Grilling surface area (mm) (WxD)-Filted collection drawer-Power rating on each oblight (N)N1.8/1x1.2Drainage tap diameter-Touch controlYesPower rating on each oblight (N)-Tank capacity (L)-Tank capacity (L)- <th></th> <th>5052263005419</th>		5052263005419
Unit external height (mm)275Packed deight (mm)465Packed height (mm)680Packed height (mm)415Product weight (kg)12Packed weight (kg)14.5Variable ControlYesEasy clean stainless steel constructionYesPower on indicator light-Non-slip feet for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UK ap in plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Gilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesPacket distributionYesPacket distributionYesPacket distributionYesPower rating on each hotplate (kW)X1.8/1x1.2Drainage tap diameter-Tank dimensions (mm) (WxDxH)-Tank dimensions (mm) (WxDH)-Head element-Head element-		400
Packed width (mm)465Packed depth (mm)680Packed height (mm)415Product weight (kg)12Packed weight (kg)14.5Variable ControlYesEasy clean stainless steel constructionYesPower on indicator light-Non-slip feet for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-MaterialInstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Plate temperature range-Touch controlYesPacket distributionYesPlate temperature range-Touch controlYesTank apacity (L)-Tank dimensions (mm) (WxDH)-Tank dimensions (mm) (WxDH)-Tank dimensions (mm) (WxDH)-Tank dimensions (mm) (WxDH)-Tank dimensions (mm) (WxD)-Hinged element-Hinged element-	Unit external depth (mm)	600
Packed depth (mm)680Packed height (mm)415Product weight (kg)12Packed weight (kg)14.5Variable ControlYesEasy clean stainless steel constructionYesPower on indicator light-Non-slip feet for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UK3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Grilling surface area (mm) (WxD)InstantGrilling surface area (mm) (WxD)YesPlate temperature range60°C to 240°CTemparatier range60°C to 240°CTemparature range60°C to 240°CTemperature range50°C to 240°CTemperature range-Max water capacity (L)-Tank dagaetty (L)-Tank dimensions (mm) (WxDH)-Tank dimensions (mm) (WxDH)-Tank dimensions (mm) (WxDH)-Tank dimensions (mm) (WxDH)-Hinged element-	• · ·	275
Packed height (mn)415Product weight (kg)12Packed weight (kg)14.5Variable ControlYesEasy clean stainless steel constructionYesPower an indicator light-Non-slip feet for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Mak heat up time (mins)InstantGrilling surface area (mm) (WXD)-Plate temperature range60°C to 240°CTemperature range-Power rating on each hotplate (kW)YesPower rating on each hotplate (kW)-Tank dimensions (mm) (WxDH)-Tank dimensions (mm) (WxDH)-Hinged element-	, , ,	465
Product weight (kg)12Packed weight (kg)14.5Variable ControlYesEasy clean stainless steel constructionYesPower on indicator light-Non-slip feet for safetyYesPower ating (kW)3.1Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CHeat up indicator light-Touch controlYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank dimensions (mm) (WxDH)-Basket size (mm) (WxD)-Hinged element-		680
Packed weight (kg)14.5Variable ControlYesEasy clean stainless steel constructionYesPower on indicator light-Non-slip feet for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Grilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank dimensions (mm) (WxDH)-Hinged element-		-
Variable ControlYesEasy clean stainless steel constructionYesPower on indicator light-Non-slip feet for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Goiling surface area (mm) (WxD)-Removable fa collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Tank capacity (L)-Tank dimensions (mm) (WxDH)-Hasket size (mm) (WxD)-Hasket size (mm) (WxDH)-Hinged element-		12
Easy clean stainless steel constructionYesPower on indicator light-Non-slip feet for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-MaterialInstantGilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating one ach hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Mak reat capacity (L)-Tank dimensions (mm) (WxDH)-Tank dimensions (mm) (WxD)-Hasket size (mm) (WxD)-Hinged element-	Packed weight (kg)	14.5
Power on indicator light-Non-slip feet for safetyYesPower rating (kW)3.1Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Contents-Material grotection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDMH)-Basket size (mm) (WxD)-Hinged element-	Variable Control	Yes
Non-slip feet for safetyYesPower rating (WU)3.1Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxD)H-Basket size (mm) (WxD)-Hinged element-	•	Yes
Power rating (kW)3.1Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank dimensions (mm) (WxDH)-Basket size (mm) (WxD)-Hinged element-		
Voltage supply (V)220/240UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank dapacity (L)-Tank dimensions (mm) (WxDH)-Basket size (mm) (WxD)-Hinged element-		
UK 3 pin plugYesFitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDH)-Basket size (mm) (WxD)-Hinged element-		
Fitted cable length (M)0.7MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank dimensions (mm) (WxDH)-Basket size (mm) (WxD)-Hinged element-		220/240
MaterialStainless SteelGastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxD)H)-Basket size (mm) (WxD)-Hinged element-		
Gastronorm trays-Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Hinged element-		
Capacity-Removable non-stick inner bowl-One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		Stainless Steel
Removable non-stick inner bowl-One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank dimensions (mm) (WxD)H)-Basket size (mm) (WxD)-Hinged element-	-	-
One touch operation-Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range 60° C to 240° CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Hinged element-		-
Thermal protection-Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Basket size (mm) (WxDXH)-Hinged element-		-
Contents-Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-	-	-
Max heat up time (mins)InstantGrilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-	-	-
Grilling surface area (mm) (WxD)-Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		
Removable fat collection drawer-Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		Instant
Plate temperature range60°C to 240°CTemperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		-
Temperature range-Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		
Heat up indicator light-Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		
Touch controlYesEven heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		
Even heat distributionYesPower rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		
Power rating on each hotplate (kW)1x 1.8/1x 1.2Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		
Drainage tap diameter-Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		
Max water capacity (L)-Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		
Tank capacity (L)-Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		-
Tank dimensions (mm) (WxDxH)-Basket size (mm) (WxD)-Hinged element-		
Basket size (mm) (WxD) - Hinged element -		
Hinged element -		-
-		
Safety cut out -	-	
	Safety cut out	-