



Dishwasher X-100

2.5 KW WASH TANK AND 7.5 KW BOILER

Commercial pass-through dishwasher with a max. loading height of up to 400 mm and 3 wash cycles with thermal cycle delay option included. A stainless steel, top of tank filter system is also included as standard.

- A hood type dishwasher for both straight in line and corner situations -suitable for washing trays, as well as all types of plates, cups, glasses and cutlery.
- Professional washing with double system of rotating wash and rinse arms top and bottom.
- Hood operated, auto cycle star. 3 wash cycles.
- Manufactured from catering grade AISI 304 2B stainless steel and incorporating top quality components.
- The inside of the machine features rounded corners, the elimination of angles avoiding the accumulation of dirt.
- Removable stainless steel rack holders ensure even distribution of wash water without dead zones. Precision positioned water jets guarantee optimum washing result for even the most stubbornly stained glasses. Easy to assemble, boltless rinse spray arms.
- A double filter system provides effective wash pump protection that is easily removed (for maintenance and cleaning) and replaced, without tools.
- Completely rounded, stainless steel wire rack support and guide.
- A magnetic micro-switch stops the wash cycle, in the event of the hood being raised prematurely.
- Standard features include adjustable feet for levelling.
- A stainless steel, top of tank filter system is also included as standard.
- Rinse aid dosing equipment.
- Adjustable washing tank and boiler temperature and security in the boiler.
- Thermal cycle delay option, guaranteeing a minimum final rinse temperature of 85°C for each and every rinse cycle.
- Sammic ware washers are designed for easy and fast on-site maintenance.
- 100% tested.



2006/95/EC, 2004/108/EC

UNE-EN 60335-2-58:1998+A1:99, UNE-EN 60335-1:1997
 UNE-EN 55014-1:2002, UNE-EN 61000-2-3:2001
 UNE-EN 61000-3-3:1997+C:99, UNE-EN 55014-2:1998



Dishwasher X-100



TECHNICAL SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm
Maximum glass height: 400 mm

Cycles: 3
Cycle duration: 60 " / 120 " / 180 "
Production baskets/hour: 60 / 30 / 20
·Boiler capacity: 10 l
·Wash tank capacity: 40 l
·water consumption/cycle: 3.5 l
Loading

·Pump: 880 W / 1.2 Hp
·Tank: 2500 W
·Boiler: 7500 W
·Total loading: 8380 W

External dimensions (WxDxH)

·Width:640 mm
·Depth: 756 mm
·Height: 1920 mm / 1468 mm

Net weight: 115 Kg
Basket dimensions: 500 mm x 500 mm
Maximum glass height: 400 mm

Cycle duration: 60 " / 120 " / 180 "
Production baskets/hour: 60 / 30 / 20

Wash temperature: 65 °C
Rinse temperature: 90 °C
·Boiler capacity: 10 l
·Wash tank capacity: 40 l
·water consumption/cycle: 3.5 l
Loading

·Pump: 880 W / 1.2 Hp
·Tank: 2500 W
·Boiler: 7500 W
·Total loading: 8380 W

External dimensions (WxDxH)

·Width:640 mm
·Depth: 756 mm
·Height: -- mm

Net weight: 115 Kg
Noise level (1m.): <70 dB(A)

DEFAULT EQUIPMENT

- Rinse aid pump.
- 1 open basket.
- 1 plate basket.
- 1 cutlery basket.
- Stainless steel top-of-tank filter set.

OPTIONAL EQUIPMENT

- Detergent dosing equipment.
- Drain pump (B).
- Booster pump (kit).
- Constant rinse temperature system with booster pump and break tank (C).
- Steam condenser unit (V).