



British Manufacturing  
since 1957



*The Professionals Choice*

# CPF4100-3

Premium Counter top, Automatic-Fill Water Boiler – with Filtration



## FULL SPECIFICATION



### CPF4100-3 Automatic Fill Water Boiler with Filtration

Type	Countertop - <i>Premium Range</i>
Country of Design & Manufacture	UK
<b>CAPACITY, WEIGHTS &amp; DIMENSIONS:</b>	
Capacity (Litres)	17
Unit dimensions (W x D x H) mm	360 x 555 x 610 (depth includes drip-tray)
Packed dimensions (W x D x H) mm	470 x 600 x 710
Tap clearance mm	200mm
Product weight - empty (kg)	17.5
Product weight – full (kg)	38.9
Packed weight (kg)	21.2
<b>CONSTRUCTION:</b>	
Outer fabrication (body) construction	304 grade Stainless Steel (Superbrush polish)
Tank construction	304 & 316 grade Stainless Steel
Tank wall thickness	0.9mm
Drip-tray	304 grade Stainless Steel – (Mirror polish)
<b>ELECTRICAL:</b>	
Power rating (kW)	3
Voltage supply	230 V (50-60Hz)
Electrical supply	Single-phase, N & E (13A)
Electrical Installation	UK standard 3-pin
Fitted cable length (m)	1.6m
<b>PLUMBING:</b>	
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4"BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	Choice of front (via drip-tray) or rear (1/2"BSP – 15mm)
<b>PERFORMANCE:</b>	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	48 mins (full tank capacity)
Output per hour (@ default temperature setting)	28 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	17 Litres
Recovery per minute	0.5 Litre
Stand-by power loss (idle mode)	0.09 kW/h
<b>FILTRATION:</b>	
Multi-Filter (taste & odour, sediment & reduces lime-scale)	Yes
Benefits of AQ35 triple-action filtration:	Removes sediment & impurities such as chlorine and reduces limescale build-up
Max recommended filter capacity	13,500 (or 6 months)
Mechanical sediment filtration	3 micron
Filter counter programmable	Yes (between 2000 & 19,500 litres)
<b>OTHER FEATURES:</b>	
7 day programmable timer	Yes
Energy saving ECO mode	Yes
Tank-baffle plates – unique design aids heat recovery & reduces steam emissions to atmosphere	Yes
Twin draw-off taps for speeds delivery	Yes
Early warning lime-scale diagnostics (via LCD)	Yes
Dual safety protection	Yes - Over-boil & boil-dry protection
<b>STANDARDS &amp; APPROVALS:</b>	
WRAS approved	Yes
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes (BS EN 60335-1 & 2)
<b>WARRANTY &amp; AFTER-SALES:</b>	
Guarantee	3 Year parts & 2 Year labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)

Instanta Limited

T: 01704 501114 F: 01704 501115 E: [sales@instanta.com](mailto:sales@instanta.com)



Certificate Numbers: FM01234 & EM01234