



Demand more. Choose Foster

MBCFT150 Modular Blast Chiller/Freezer

MBCFT150



Temperature



Blast Chiller - Freezer 70/-18 °C

Dimensions (mm)

W 1350 D 1330

H 2350



Capacity

undefined Litres

150 Freezing (Kg)

Unpacked Weight

790 KG

Features & Benefits

Our Modular Blast Chill/Freeze range is designed to cope with the multi-purpose requirement of the foodservice industry, and enables you to take control of the Cook-Chill Process

- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status.
- Capable of blast chilling from +70°C to +3°C in 90 minutes
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Operator-friendly fans cut-out whenever door is opened
- HACCP software is available as an option in 3 formats for data retrieval and management

| External Finish | |
|----------------------|----------|
| 304 Stainless Steel | Option |
| Stainless Steel Door | Option |
| Foodsafe | Standard |

| Internal Finish | |
|---------------------|----------|
| 304 Stainless Steel | Option |
| Foodsafe | Standard |

| Shelving | |
|------------------|--------------|
| Trolley Capacity | Not Supplied |
| - | |
| 690x1040x1890 | |

| Doors | |
|---------------------|----------|
| Solid Full | Standard |
| Hinged - Right Hand | Standard |
| Hinged - Left Hand | Option |
| Pass Through | Option |

| Refrigeration | |
|-------------------------------|----------|
| Forced Air | Standard |
| Remote - less condensing unit | Standard |
| R404a | Standard |

| Electrical Data & Service Information | |
|---------------------------------------|----------|
| 230 Volts | Standard |
| 50Hz | Standard |
| 1 Phase | Standard |
| Running Watts | 4767 |
| Running Amps | 18.3 |
| Thermal Heat Rejection (W) | 5,607 |
| Noise (dBa @ 1m) | TBC |
| Fuse Required (A) | N/A |

| Product Extras | |
|------------------------------------|----------|
| Door Pull Handle | Standard |
| Hold Facility | Option |
| Temperature Probe | Option |
| Hardwired Logging System Interface | Option |
| Food Probe | Option |
| Anti Condensation on Control Panel | Option |

Footnotes

- MBC models are supplied floorless for blast chilling application only. MBCF models are supplied complete with 25mm floor and are suitable for occasional blast freezing and non-ground floor sites
- Control panel sprayed white
- Capacity 150kg. Chilling capacity 70oC to 3oC in less than 90 minutes within specifications. Entry temperature or up to 90oC for chilling. Freezing capacity from 70oC to -18oC in less than 240 minutes within specifications
- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15oC e.g. Prep rooms
- Condensing Unit: All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral).

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster

