



Demand more. Choose Foster

MBCT150 Modular Blast Chiller

MBCT150



Temperature



Blast Chiller 70/3 °C

Dimensions (mm)

W 1350 D 1330

H 2350



Capacity

undefined Litres

150 Chilling (Kg)

Unpacked Weight

790 KG

Features & Benefits

Our Modular Blast Chill/Freeze range is designed to cope with the multi-purpose requirement of the foodservice industry, and enables you to take control of the Cook-Chill Process

- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status.
- Capable of blast chilling from +70 $^{\circ}\text{C}$ to +3 $^{\circ}\text{C}$ in 90 minutes
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Operator-friendly fans cut-out whenever door is opened
- HACCP software is available as an option in 3 formats for data retrieval and management

External Finish	
304 Stainless Steel	Option
Stainless Steel Door	Option
Foodsafe	Standard

Internal Finish	
304 Stainless Steel	Option
Foodsafe	Standard

Shelving	
Trolley Capacity	Not Supplied
-	
690x1040x1890	

Doors	
Solid Full	Standard
Hinged - Right Hand	Standard
Hinged - Left Hand	Option
Pass Through	Option

Refrigeration	
Forced Air	Standard
Remote - less condensing unit	Standard
R404a	Standard

Electrical Data & Service Information	
230 Volts	Standard
50Hz	Standard
1 Phase	Standard
Running Watts	867
Running Amps	1.3
Thermal Heat Rejection (W)	1,707
Noise (dBa @ 1m)	TBC
Fuse Required (A)	0 amp

Product Extras	
Door Pull Handle	Standard
Hold Facility	Option
Temperature Probe	Option
Hardwired Logging System Interface	Option
Food Probe	Option
Anti Condensation on Control Panel	Option

Footnotes

- MBC models are supplied floorless for blast chilling application only. MBCF models are supplied complete with 25mm floor and are suitable for occasional blast freezing and non-ground floor sites
- Control panel sprayed white
- Capacity 150kg. Chilling capacity 70oC to 3oC in less than 90 minutes within specifications. Entry temperature or up to 90oC for chilling.
- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15oC e.g. Prep rooms
- Condensing Unit: All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral).

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster

