

# British Manufacturing since 1957



### The Professionals Choice

## **CPF310**

Premium Counter top, Automatic-Fill Water Boiler – with Filtration



#### **FULL SPECIFICATION**



### **CPF310** Automatic Fill Water Boiler with Filtration

Туре	Countertop - Premium Range
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	
Capacity (Litres)	10
Unit dimensions (W x D x H) mm	260 x 555 x 705 (depth includes drip-tray)
Packed dimensions (W x D x H) mm	360 x 595 x 830
Tap clearance mm	304mm (extra clearance for tall jugs, teapots & cafetieres)
Product weight - empty (kg)	16.8
Product weight – full (kg)	31.5
Packed weight (kg)	19.6
CONSTRUCTION:	
Outer fabrication (body) construction	304 grade Stainless Steel (Superbrush polish)
Tank construction	304 & 316 grade Stainless Steel
Tank wall thickness	0.9mm
Drip-tray	304 grade Stainless Steel – (Mirror polish)
ELECTRICAL:	Con grado etamioso eteon (minor peneri)
Power rating (kW)	6
Voltage supply	230 V (50-60Hz)
Electrical supply	Single-phase, N & E (25A)
Electrical Installation	Wire to 30A single-phase supply via an isolation switch
Fitted cable length (m)	1.6m (3-core HR @ 2.5 <sup>2</sup> mm)
PLUMBING:	1.0111 (0 0010 1111 (@ 2.0 111111)
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4"BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	Choice of front (via drip-tray) or rear (1/2"BSP – 15mm)
PERFORMANCE:	choice of front (via any day) of roar (172 Bot Tollin)
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	16 mins (full tank capacity)
Output per hour (@ default temperature setting)	57 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	11 Litres
Recovery per minute	1 Litre
Stand-by power loss (idle mode)	0.084 kW/h
FILTRATION:	0.00 T KT////
Multi-Filter (taste & odour, sediment & reduces lime-scale)	Yes
Filter Benefits	Latest triple-action; removes sediment & impurities such as
THE BOTTOM	chlorine and reduces limescale build-up
Max recommended filter capacity	13,500 (or 6 months)
Mechanical sediment filtration	3 micron
Filter counter programmable	Yes (between 2000 & 19,500 litres)
OTHER FEATURES:	100 (301110011 2000 31 10,000 111100)
7 day programmable timer	Yes
Energy saving ECO mode	Yes
Tank-baffle plates – unique design aids heat recovery &	Yes
reduces steam emissions to atmosphere	· · ·
Early warning lime-scale diagnostics (via LCD)	Yes
Dual safety protection	Yes - Over-boil & boil-dry protection
STANDARDS & APPROVALS:	7,
WRAS approved	Yes
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes (BS EN 60335-1 & 2)
WARRANTY & AFTER-SALES:	,
	3 Year parts & 2 Year labour
Guarantee Spare parts, filters & accessories	3 Year parts & 2 Year labour Same day despatch (if ordered before 3pm)

Instanta Limited

**T**: 01704 501114 **F**: 01704 501115 **E**: <u>sales@instanta.com</u>



