



DYNAMIC PREPARATION

TECHNICAL SPECIFICATIONS

External dimensions

·Width: 280 mm

·Depth: 512 mm

·Height: 735 mm Net weight: 3,9 Kg

Hourly production: 100 Kg - 150 Kg

HAND OPERATED POTATO CHIPPING MACHINE



Potato Chipping Machine CF-5

MAKE PERFECT FRENCH FRIES FOR RESTAURANTS AND LARGE KITCHENS.

Output: 100 - 150 Kg./h.

Equipped with a knife block and pusher set.

- · Light stainless alloy body: light and strong.
- · Clean cut, without breaching or throw-away and without fatigue.
- · The use of exchangeable knife blocks and pusher sets allows thicknesses of 8, 10 or 12 mm to be achieved.
- · Controls and nuts and bolts in stainless steel.
- \cdot The pusher ejects the chips and leaves the grid free.
- · Extended handle which provides optimal results with minimal effort.
- · Comfortable use: The springs at the rear leave the grid completely free.
- · The springs are highly flexible compensators which help to raise the presserejector.
- · Equipped with suction feet to provide stability on the work surface.
- \cdot Easy to clean.
- · Blade units of various sizes and holding bowls for cut potatoes are available as optional accessories.

DEFAULT EQUIPMENT

- 1 Knife block + pusher set.
- OPTIONAL EQUIPMENT
- Knife block + pusher sets of different sizes.
 Recipient for cut potato. (See gastronorm continers, maximum 1/1 65mm)









NSF/ANSI Standard 169.

1935/2004 CE, 2001/95 CE UNE-EN 601:2005