



P6B4 - Panther 670

Series Free-standing Hot Cupboard - Bain Marie Top - 4GN - W 1530 mm - 4.9 kW

A great solution for holding and transporting food at the perfect temperature, the Panther 670 Series Hot Cupboard / Bain Marie is designed to fit through narrow doorways, so is ideal for pubs and smaller restaurants as well as nursing and care homes where plated meals are to be transported from the kitchen to the residents.

- ✓ Ideal to fit through narrow corridors and doorways
- ✓ Bain marie top, ideal for small restaurants, cafes and pubs, as well as nursing and care homes, where the easy transportation of plated meals to diners and residents is a necessity
- ✓ Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- ✓ Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 4 x 1/1 GN containers up to 150mm deep.
- ✓ Thermostatically controlled bain marie top can be operated with wet or dry heat. Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 degrees C, ensures compliance with food hygiene regulations
- ✓ Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- ✓ Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads
- ✓ Drain tap located inside the hot cupboard allows fast and easy draining

Specifications

Summary

Range Name	Panther
Power Type	Electric
Unit Type	Free-standing
Available in UK Only	No
UK Warranty	2 Years Parts and Labour Warranty
Export Warranty	Contact your local dealer
GTIN Code	5056105103417

Power and Performance

Gastronorm Capacity	4 x GN1/1
Total Power kW	4.9
Temperature Range °C	20 - 99
IP Rating	IP24
Plate Capacity	382
Temperature Control	Top: Mechanical/Bottom: Electronic

Key Specifications

Drain Location	Right side interior mounted
Number of Shelves included	2
Number of Shelf Positions	4
Pot Type	Gastronorm
Type of Heat	Wet/Dry
Heated Base	Yes
Heated Gantry	No
Static or Mobile	Mobile




Weights and Dimensions

Unit Height (External) mm	912
Unit Width (External) mm	1530
Unit Depth (External) mm	672
Height (Internal) mm	432
Width (Internal) mm	1345
Depth (Internal) mm	512
Shelf Dimensions Width mm	1286
Shelf Dimensions Depth mm	512
Net Weight Kg	116.5

Supply Connections		Shipping	
Requires Installation	Yes	Packed Weight Kg	136.5
Requires Electrical Supply	Yes	Packed Height cm	110
UK 3 Pin Plug	No	Packed Width cm	155
Requires Hardwiring	Yes	Packed Depth cm	90
Electrical Supply Rating Watts	4,950		
Single Phase Amps	21.5		
Single Phase Voltage	230		

Available Options	
Overshelf or Gantry	
PG4A	PG4A - Ambient Gantry
PG4H	PG4H - Heated Gantry
PS4A1	PS4A1 - 1 Ambient Overshelf
PS4A2	PS4A2 - 2 Ambient Overshelves
PS4A3	PS4A3 - 3 Ambient Overshelves
PS4H1	PS4H1 - 1 Heated Overshelf
PS4H2	PS4H2 - 2 Heated Overshelves
PS4H3	PS4H3 - 3 Heated Overshelves
Door Locks	
PDL4	PDL4 - Lockable Door
Corner Guards	
PCG	PCG - Corner Guards [Set of Four]
Trayslides	
PTS4	PTS4 - Tray Slide
Legs/Castors	
PLK	PLK - Legs [non chargeable]

Available Accessories	
CP16	CARVERY PAD 1/1 GAST
PGK1	GN PACK 1
PGK10	1 x PGK1 + 1 x PGK3
PGK11	1 x PGK2 + 1 x PGK3
PGK12	2 x PGK3
PGK2	GN PACK 2
PGK3	GN PACK 3
PGK8	2 x PGK1
PGK9	1 x PGK1 + 1 x PGK2
PHTC	PANTHER - CERAMIC INSERT - 1/1 GN SIZE CERAMIC INSERT
PHTG	PANTHER - GLASS INSERT - 1/1 GN SIZE GLASS INSERT
PLK/S	PANTHER LEG KIT FOR CONVERSION IN THE FIELD



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm