



Demand more. Choose Foster

MBCT250W Modular Blast Chiller (with 900mm wide door)

MBCT250W



Temperature

 Blast Chiller 70/3 °C

Dimensions (mm)

W 1550 D 2330

H 2350



Capacity

250 Chilling (Kg)

Unpacked Weight

790 KG

Features & Benefits

Our Modular Blast Chill/Freeze range is designed to cope with the multi-purpose requirement of the foodservice industry, and enables you to take control of the Cook-Chill Process

- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status.
- Capable of blast chilling from +70°C to +3°C in 90 minutes
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Operator-friendly fans cut-out whenever door is opened
- HACCP software is available as an option in 3 formats for data retrieval and management

External Finish		Doors		Electrical Data & Service Information	
304 Stainless Steel	Option	Solid Full	Standard	400 Volts	Standard
Stainless Steel Door	Option	Hinged - Right Hand	Standard	50Hz	Standard
Foodsafe	Standard	Hinged - Left Hand	Option	3 Phase	Standard
Foodsafe	Standard	Pass Through	Option	Running Watts	1707
Internal Finish		Refrigeration		Running Amps	1.3
304 Stainless Steel	Option	Forced Air	Standard	Thermal Heat Rejection (W)	3,387
Foodsafe	Standard	Remote - less condensing unit	Standard	Noise (dBa @ 1m)	TBC
Shelving		R404a	Standard	Fuse Required (A)	0 amp
Trolley Capacity	Not Supplied			Product Extras	
-				Door Pull Handle	Standard
890x1040x1890				Hold Facility	Option
				Temperature Probe	Option
				Hardwired Logging System Interface	Option
				Food Probe	Option
				Anti Condensation on Control Panel	Option

Footnotes

- MBC models are supplied floorless for blast chilling application only. MBCF models are supplied complete with 25mm floor and are suitable for occasional blast freezing and non-ground floor sites
- Control panel sprayed white
- Capacity 250kg. Chilling capacity 70oC to 3oC in less than 90 minutes within specifications. Entry temperature or up to 90oC for chilling.
- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15oC e.g. Prep rooms
- Condensing Unit: All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral).

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster

