



Product Code: EP700HL 10-137

EcoPro G2 600 Litre Upright Dual Temp Cabinet

---



## Features & Benefits

---

- Dual temperature option offers refrigerator and freezer temperatures in the same cabinet perfect when space is at a premium
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet

## External Finish

s/steel ext, 304 s/s door	Standard
304 S/S back for island sitting	Option

## Base Fittings

Castors 80mm	Standard
--------------	----------

## Electrical, Service & Ecodesign Data

230/50/1	Standard
220/60/1 Electrical Supply	Option
Fuse Required	13

## Internal Finish

aluminium	Standard
-----------	----------

## Doors

Solid	Standard
-------	----------

Left Hand Hinged Door	Option
-----------------------	--------

## Product Extras

Helicoil Mains Lead	Option
---------------------	--------

## Shelving

Additional S/S Trayslides	Option
---------------------------	--------

Additional GN2/1 Shelf	Option
------------------------	--------

## Refrigeration

R134a/R404a	Standard
-------------	----------

Less Condensing Unit	Option
----------------------	--------

## Specification

Dimensions (Width)	700
--------------------	-----

Dimensions (Height)	2080
---------------------	------

Dimensions (Depth)	840
--------------------	-----

Weight (Unpacked, kg)	155
-----------------------	-----

Weight (Packed, kg)	167
---------------------	-----

Gross Volume	600
--------------	-----

Noise DbA @ 1M	TBC
----------------	-----

## Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



Energy



Quality



Value



Design



Hygiene



After Care