



Demand more. Choose Foster

Foster Display Chiller 1500mm Closed Front Assisted Service FDC1500C



Temperature



Refrigerator 1/4 °C

Dimensions (mm)

W 1500 D 785

H 1435



Capacity

200 Litres

Unpacked Weight

Features & Benefits

In its closed front format, the Foster Display Chiller provides a stylish solution to the demands of assisted service: showing your customers the best possible view of your food, in an ergonomically designed easy access display. Fresh is always best, and with the closed front design, your pre-prepared cakes, pastries and delicatessen can stay at their best without compromising your service times.

- ACT (Anti Condensation Technology) helps glass to remain clear, maximising product display
- Glass end panels over 70% wider than many models in the market, maximising your display window
- Thick toughened glass for enhanced safety across both open and closed fronted models
- Manufactured using superior 304 stainless steel – the 'gold standard' in performance finishes meaning quality is assured
- Foster's innovative air curtain protects your merchandise from warmer air entering the display ensuring your food keeps both its taste and texture
- Brilliantly bright LED lighting in top canopy and on every shelf significantly enhances product display
- Innovative design means the controller can be positioned to the front or rear – allowing on site flexibility
- There when you need us: Unrivalled 2 year parts and labour warranty as standard for complete peace of mind (UK only)

| External Finish | | |
|------------------------------------|-------------|----------|
| 304 Stainless Steel | | Standard |
| Internal Finish | | |
| 304 Stainless Steel | | Standard |
| Shelving | | |
| 10mm Thick Glass Shelving | Quantity: 3 | Standard |
| Base Fittings | | |
| Roller Castors | | Standard |

| Refrigeration | | |
|----------------|--|----------|
| Forced Air | | Standard |
| Integral | | Standard |
| Depth Note: | The unit is designed to operate at M2 temperature requirements (EN441 Climate Class 3 25° ambient) | |
| R404a | | Standard |

| Electrical Data & Service Information | | |
|---------------------------------------|--|----------|
| 230 Volts | | Standard |
| 50Hz | | Standard |
| 1 Phase | | Standard |
| Fuse Required (A) | | 13 amp |

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster