



Glasswasher X-41

400X400MM RACKS. USEFUL HEIGHT: 280MM

**Top + bottom wash arms.
3 wash cycles.
Cold rinse facility.
Option of built-in water softener.**

- For washing glasses, cups, cutlery and small plates.
- 3 wash cycles with final cold rinse.
- Manufactured from catering grade AISI 304 2B stainless steel and incorporating top quality components.
- Double skinned door with high efficiency seal, ensuring thermal and acoustic insulation. Magnetic door micro-switch.
- Removable stainless steel rack holders ensure even distribution of wash water without dead zones. Precision positioned water jets guarantee optimum washing result for even the most stubbornly stained glasses. Easy to assemble, boltless rinse spray arms.
- Rinsing dispensers without screws, easy assembly and simple and clean look.
- A double filter system provides effective wash pump protection that is easily removed (for maintenance and cleaning) and replaced, without tools.
- Completely rounded, stainless steel wire rack support and guide.
- Automatic rinse aid dosing equipment.
- Electronic control panel with anti-moisture seal.
- Adjustable washing tank and boiler temperature and security in the boiler.
- Rinse boiler temperature adjustment and a thermal cycle delay option, guaranteeing a minimum final rinse temperature of 85°C for each and every rinse cycle.
- Sammic ware washers are designed for easy and fast on-site maintenance.



2006/95/EC, 2004/108/EC

UNE-EN 60335-2-58:1998+A1:99, UNE-EN 60335-1:1997
UNE-EN 55014-1:2002, UNE-EN 61000-2-3:2001
UNE-EN 61000-3-3:1997+C:99, UNE-EN 55014-2:1998



Glasswasher X-41



TECHNICAL SPECIFICATIONS

Basket dimensions: 400 mm x 400 mm
Maximum glass height: 280 mm

Cycle duration: 120 " / 180 " / 130 "
Production baskets/hour: 30 / 20 / 27

water consumption/cycle: 2.2 l

Loading

- Pump: 240 W / 0.33 Hp
- Tank: 1500 W
- Boiler: 2500 W
- Total loading: 2740 W

External dimensions

- Width: 470 mm
- Depth: 535 mm
- Height: 710 mm

Net weight: 42 Kg
Noise level (1m.): <70 dB(A)

DEFAULT EQUIPMENT

- Rinse aid doser.
- Variable detergent dosing equipment.
- 1 open basket.
- 1 mixed basket.
- 1 small cutlery basket.

OPTIONAL EQUIPMENT

- Models with built-in water softener available.
- Model with drain pump and non-return available.
- Stand.
- High feet kit 140-190mm.