



PLATINUM

FREESTANDING PLATINUM FREEZER SOLID DOOR 600L STAINLESS STEEL



- ✓ **Large 600L Capacity**
offers maximum frozen storage space
- ✓ **-18°C to -25°C Temperature Range**
allows user to select ideal temperature
- ✓ **6 Fixed Height Shelves**
for effective stock control
- ✓ **Stylish Integrated Handle**
for ease of opening
- ✓ **2/1 Gastronorm Compatible**
- ✓ **4 Fitted Castors**
with two locking at front for ease of movement
- ✓ **Lockable**
- ✓ **Replaceable Door Seal**
- ✓ **Self Closing Door**
means door cannot be left open accidentally,
spoilng contents
- ✓ **Manual Defrost**
for low on-going maintenance
- ✓ **Warning Alarms**
high/low temperature and door open alarms to
alert users to a problem

SKU CODE:	PRODUCT CODE:	DESCRIPTION:
444441149	CFS600ST	Freestanding Platinum Freezer Solid Door 600L Stainless Steel



FULL SPECIFICATION – CFS600ST FREESTANDING PLATINUM FREEZER SOLID DOOR 600L STAINLESS STEEL

Description	Freestanding
SKU Code	444441149
EAN Code	5052263011496
GDPA Code	CFS600ST
Unit External Width (mm)	775
Unit External Depth (mm)	743
Unit External Height (mm)	1982
Packed Width (mm)	835
Packed Depth (mm)	782
Packed Height (mm)	1995
Product Weight (kg)	105
Packed Weight (kg)	129
Internal Dimensions (mm) (WxDxH)	645x528x1646
Gross Capacity (L)	600
Net Capacity (L)	561
Material - Exterior Finish	Stainless Steel
Material - Interior Finish	Plastic (HIPS/ABS Mix)
Stackable	No
Gastronorm Compatible	Yes (2/1)
Colour	Stainless Steel
Internal Temperature Range	-18°C to -25°C
Maximum Ambient Operating Temperature	Up to 38°C
Defrost Type	Manual
Forced Air Cooling (Fan)	Yes
Door Type	Solid
Door Style	Hinged, reversible
Self Closing Door	Yes
Door Open Depth (mm)	1480
Replacement Door Seal	Yes
Controller type	Electronic
Open Door Sensor/Alarm	Yes
Hi/Low Temperature Alarm	Yes
External Temperature Display	Yes
Rollers/Castors	4 fitted castors (2 lockable fronts)
Number of Shelves	6
Number of Shelf Positions	Fixed
Shelf Size (mm) (WxD)	585x493
Shelf Material	Painted Aluminium
Internal LED Light	No
Light Activation	-
Fitted Lock	Yes
Insulation Thickness (mm)	65
Insulation Material	Pentane
Voltage Supply	220/240v
Power Rating (kW)	0.26
Supplied with Fitted UK Plug	Yes
Fitted Cable Length (m)	1.8
Refrigerant Type	R134a
CFC Free	Yes
HFC Free	No
HCFC Free	Yes
Ammonia Free	Yes
Heat Rejection (Watts)	260
Energy Consumption (Kw/h) (24hrs)	3.3