

Product Code: FS90 27-108

Air cooled standard Ice Cuber



Features & Benefits

FS90

- · Innovatively designed with new user-friendly electro-mechanical controls to ensure reliability
- The models also incorporate a condenser thermostat, which ensures a full harvest of cubes
- Produces ultra cold square cubes that last longer in the glass, ice bucket and the machine's storage bin
- Uses as little as 5 litres of water to produce 1 kilo of ice important where water is metered.
- The new flush system ensures clear ice free from impurities and eliminates the risk of lime-scale
- Bin capacity: 42kgs
- Ice: Cubed 35x37x32mm

External Finish		Internal Finish		Refrigeration	
Stainless steel	Standard	N/A	Standard	R134a - Industry Standard	Standard
Electrical, Service & Ecodesign Data		Specification		Drain Rqd	20mm
				Integral	Standard
		Dimensions (Width)	700	Integral Refrigeration System	Standard
230/50/1	Standard	Dimensions (Height)	995		
Fuse Required	13	Dimensions (Depth)	580		
		Cube - 31 x 24 x 26mm	Standard		
		Noise Dba @ 1M	TBC		
		KG per 24 hours	82		

Footnotes

- Output figures quoted are based on 10°C water input and ambient air temp of 21°C
- Dimensions: Legs provided as standard to increase height for drainage where required 120cm maximum height increase
- Note: A minimum clearance of 15cm (6") must be left at the sides of the machine for routing cooling air drawn into and exhausted out of the compartment to maintain a proper condensing operation
- Maximum ambient air temperature 40°C; maximum input water temperature 35°C



Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU Phone 08432 168800 | Email sales@foster-uk.com | Visit www.fosterrefrigerator.com