

British Manufacturing since 1957



The Professionals Choice

CPF520-3

Premium Counter top, Automatic-Fill Water Boiler (High Taps) – with Filtration



FULL SPECIFICATION



CPF520-3 Automatic Fill Water Boiler (High Taps) with Filtration

Туре	Countertop - Premium Range
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	OK .
	17
Capacity (Litres) Unit dimensions (W x D x H) mm	
	360 x 555 x 705 (depth includes drip-tray) 470 x 600 x 820
Packed dimensions (W x D x H) mm	304mm
Tap clearance mm	18.9
Product weight - empty (kg)	
Product weight – full (kg)	40.0
Packed weight (kg)	23.4
CONSTRUCTION:	
Outer fabrication (body) construction	304 grade Stainless Steel (Superbrush polish)
Tank construction	304 & 316 grade Stainless Steel
Tank wall thickness	0.9mm
Drip-tray	304 grade Stainless Steel – (Mirror polish)
ELECTRICAL:	
Power rating (kW)	3
Voltage supply	230 V (50-60Hz)
Electrical supply	Single-phase, N & E (13A)
Electrical Installation	UK standard 3-pin
Fitted cable length (m)	1.6m
PLUMBING:	
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4"BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	Choice of front (via drip-tray) or rear (1/2"BSP - 15mm)
PERFORMANCE:	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	48 mins (full tank capacity)
Output per hour (@ default temperature setting)	28 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	17 Litres
Recovery per minute	0.5 Litre
Stand-by power loss (idle mode)	0.09 kW/h
FILTRATION:	0.00 KW/II
Multi-Filter (taste & odour, sediment & reduces lime-scale)	Yes
Benefits of AQ35 triple-action filtration:	Removes sediment & impurities such as chlorine and
Deficition of AQ00 triple-action filtration.	reduces limescale build-up
Max recommended filter capacity	13,500 (or 6 months)
Mechanical sediment filtration	3 micron
Filter counter programmable	Yes (between 2000 & 19,500 litres)
	165 (Detween 2000 & 13,300 littles)
OTHER FEATURES: 7 day programmable timer	Yes
,, ,	
Energy saving ECO mode	Yes
Tank-baffle plates – unique design aids heat recovery &	Yes
reduces steam emissions to atmosphere	V
Twin draw-off taps for speeds delivery	Yes
Early warning lime-scale diagnostics (via LCD)	Yes Voc. Over heil & heil dry protection
Dual safety protection	Yes - Over-boil & boil-dry protection
STANDARDS & APPROVALS:	Vaa
WRAS approved	Yes
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes (BS EN 60335-1 & 2)
WARRANTY & AFTER-SALES:	
Guarantee	3 Year parts & 2 Year labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)

Instanta Limited

T: 01704 501114 **F**: 01704 501115 **E**: <u>sales@instanta.com</u>



