


Demand more. Choose Foster

Foster Pro 1800 Multideck with Nightblind and Glass FMPRO1800NG



Temperature



Dimensions (mm)



Capacity

948 Litres

Unpacked Weight

330 KG

Features & Benefits

The Foster Pro is the ultimate, large capacity Multideck product. With all the engineering know-how that you've come to expect from Foster, the Pro range offers ultimate capacity, ultimate reliability and ultimate quality. The Pro range achieves remarkable storage through intelligent, economical design solutions. With five display levels maximising capacity, the Pro is in a league of its own.

- 2x vertical side mounted full length LED lights
- Energy saving retracting 'Soft Closing Mechanism' Nightblind.
- Fully removable shelves and supports for ease of cleaning.
- Made of high quality food safe superior 'brushed' stainless steel finish for easy wipe-clean efficiency.
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time. Also our After Sales Support is there when you need us: 2 years parts and labour warranty as standard.

| External Finish | | | |
|--------------------------------------------|-------------|----------|--|
| 304 Stainless Steel | | Standard | |
| Internal Finish | | | |
| 304 Stainless Steel | | Standard | |
| Shelving | | | |
| Shelves (Including Base as shelf) | Quantity: 5 | Standard | |
| Base Fittings | | | |
| Castors | | Standard | |

| Refrigeration | | | |
|---------------|--------------------------------|--|--|
| Integral | Standard | | |
| Depth | Please allow an additional | | |
| Note: | 60mm to the depth of the | | |
| | product as spacers are | | |
| | required for air circulation | | |
| | (fitted as standard). The unit | | |
| | is designed to operate | | |
| | between +2/+4°c, in EN441 | | |
| | Climate Class 3 25° | | |
| | ambient 60% RH. | | |
| R404a | Standard | | |

| Electrical Data & Service Information | | |
|---------------------------------------|----------|--|
| 230 Volts | Standard | |
| 50Hz | Standard | |
| 1 Phase | Standard | |
| Running Watts | 2087 | |
| Running Amps | 9.2 | |
| Thermal Heat Rejection (W) | 2,186 | |
| Noise (dBa @ 1m) | TBC | |
| Fuse Required (A) | 13 amp | |

Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wall-sited.
- Delivery to dealer premises/direct to site on route days free of charge. Delivery and installation to ground floor site as priced see UK price list for conditions.

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: 0843 216 8800 Facsimile: 0843 216 4700 Email: sales@foster-uk.com















Demand more. Choose Foster