



solo per professionisti

Sirman Spa
Viale dell'industria 9/11
35010 Pieve di Curtarolo (PD) Italy
Tel. +39 049 9698666
Fax. +39 049 9698688
E-mail. info@sirman.com

CANOVA 300



- Rounded design and no sharp edges and visible screws
- Chrome plated and ground slide rod.
- Self lubricating slide rod bushings.
- Vulcanized rubber stops on carriage.
- Removable support cover for thickness gauge plate.
- Stainless steel slice deflector with bayonet fitting
- Stainless steel screws and fittings.
- Enclosed and sealed belt pulley.
- 41 mm distance between blade and motor.
- Bottom cover.
- Built in sharpening tool with bottom protection.
- Standard blade removal tool.
- 38° blade inclination
- Plastic knob.
- Controls IP 44.

DETAILS






Remarkable clearance between blade and machine body



Large hopper

TECHNICAL DATA



Model	CANOVA 300
Ø blade	mm 300 - inch. 12
Motor	watt 210 - Hp 0,29
Cut thickness	mm 20
Run of carriage	mm 275
Hopper	mm 240x230
A	mm 428
B	mm 290
C	mm 590
D	mm 495
E	mm 355
F	mm 640
G	mm 495
X	mm 230
Y	mm 175
H	mm 220
W	mm 200
Net weight	kg 26,5
Shipping	mm 800x600x520