



Vacuum Sealer SU-416

TECHNICAL SPECIFICATIONS

Pump capacity: 16 m³/h
 Bar length: 420 mm
 Total loading: -- W
 Vacuum pressure (maximum): 2 mbar

Internal dimensions

·Width: 430 mm
 ·Depth: 415 mm
 ·Height: 180 mm

External dimensions (WxDxH)

·Width: 484 mm
 ·Depth: 529 mm
 ·Height: 448 mm

Net weight: 65 Kg
 Noise level (1m.): 75 dB(A)
 Background noise: 32 dB(A)



DEFAULT EQUIPMENT

- BUSCH pump.
- Sensor Controls.
- 25 programmable settings.
- Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- Soft air function.
- Clear methacrylate lid.
- "PAUSE" function.
- Liquid detection system.

OPTIONAL EQUIPMENT

- Inert gas
- Printer
- Vacuum packing bags
- External vacuum kit for Vac-Norm, containers and accessories
- Bag cutting kit
- Support for liquid packaging
- Additional filling plates



Vacuum Sealer SU-416

TABLETOP MODEL. 16 M³/H. 420 MM.

**420 mm. sealing bar.
16 m³/h Busch vacuum pump.
Vacuum controlled by sensor.**

- Powered by Busch.
- Vacuum controlled by sensor.
- Vacuum PLUS.
- LCD colour screen: all information at a glance.
- Backlit touch keyboard.
- Programmable: 25-programme memory. Blocking option.
- "Pause" button.
- Phased vacuum programme.
- Detection of the evaporation of liquids.
- Double seal.
- Cordless sealing bar.
- Progressive decompression.
- Vac-Norm ready with Automatic decompression.
- Stainless steel body and chamber. Deep-drawn chamber.
- Damped transparent lid of high durability polycarbonate.
- Dry-oil programme for drying the pump.
- Working hours counter for oil changes.
- Safety system with protection against vacuum failure.



SAMMIC, S.L.
Basarte, 1 - 20720 AZKOITIA
www.sammic.com

