



# Product Code: EP700HU 10-125

## EcoPro G2 600 Litre Upright Undermount Refrigerated Cabinet

---



### Features & Benefits

---

- Provides an alternative format for high ambients as it takes cooler air from floor level
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circular II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

## External Finish

s/steel ext, 304 s/s door	Standard
304 S/S back for island sitting	Option

## Base Fittings

Castors 80mm	Standard
Levelling Bolts	Standard

## Electrical, Service & Ecodesign Data

230/50/1	Standard
220/60/1 Electrical Supply	Option
Fuse Required	13
Global Warming Potential	1430
Energy Efficiency Index	61.31
Refrigerant Charge	0.275
kWh (24 hours)	2.16

## Internal Finish

aluminium	Standard
-----------	----------

## Doors

Solid	Standard
Left Hand Hinged Door	Option

## Product Extras

Helicoil Mains Lead	Option
---------------------	--------

## Shelving

Additional S/S Trayslides	Option
Additional GN2/1 Shelf	Option

## Refrigeration

R134a - Industry Standard	Standard
Less Condensing Unit	Option

## Specification

Dimensions (Width)	700
Dimensions (Height)	1980
Dimensions (Depth)	865
Weight (Unpacked, kg)	121
Weight (Packed, kg)	132.6
Gross Volume	600
Noise DbA @ 1M	67.2

## Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



## Application

This appliance is intended for use in ambient temperatures up to 40°C

## Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

## Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care