



Product Code: EP1440HU

EcoPro G2 1350 Litre Upright Undermount Refrigerated Cabinet

---



## Features & Benefits

---

- Sleek, modern aesthetics, robust construction and market leading capacity. 'Smartphone style' fuzzy logic II touch sensitive control panel with high visibility temperature display
- Low energy refrigerant system with reduced running costs
- Improved internal fittings for easy cleaning
- Foster Circular II air distribution system maximises efficient operation even when shelves are fully loaded
- Operates efficiently in ambients up to 43°C
- Provides an alternative format for high ambients as it takes cooler air from floor level
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

## External Finish

s/steel ext, 304 s/s door	Standard
304 s/s	Option
304 S/S back for island sitting	Option

## Base Fittings

Castors 80mm	Standard
Legs 150mm	Option
Levelling Bolts	Standard

## Electrical, Service & Ecodesign Data

230/50/1	Standard
220/60/1 Electrical Supply	Option
Fuse Required	13
Global Warming Potential	1430
Energy Efficiency Index	107.32
Refrigerant Charge	0.320

## Internal Finish

aluminium	Standard
304 s/s	Option

## Doors

Solid	Standard
-------	----------

## Product Extras

Helicoil Mains Lead	Option
---------------------	--------

## Shelving

Additional S/S Trayslides	Option
Additional GN2/1 Shelf	Option

## Refrigeration

R290 - Energy Efficient	Standard
R134a - Industry Standard	Option
Integral Refrigeration System	Standard
Less Condensing Unit	Option
Remote Refrigeration System	Option

## Specification

Dimensions (Width)	1440
Dimensions (Height)	1980
Dimensions (Depth)	865
Weight (Unpacked, kg)	182.5
Weight (Packed, kg)	199.1
Gross Volume	1350
Noise DbA @ 1M	TBC

## Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



## Application

This appliance is intended for use in ambient temperatures up to 40°C

## Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

## Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care