



Dishwasher P-50

500X500MM. RACKS. USEFUL HEIGHT: 330MM.

Professional Washing with Total Guarantee.

- For washing glasses, cups, cutlery and small plates.
- Washing with double system of rotating dispersers (top and bottom).
- 1 wash cycle.
- Manufactured from catering grade AISI 304 2B stainless steel and incorporating top quality components.
- Double skinned door with high efficiency seal, ensuring thermal and acoustic insulation. Magnetic door micro-switch.
- Precision positioned water jets guarantee optimum washing result for even the most stubbornly stained glasses. Easy to assemble, boltless rinse spray arms.
- Inside of the machine with rounded finished: absence of angles avoiding the accumulation of dirt.
- Automatic rinse aid dosing equipment.
- Sammic ware washers are designed for easy and fast on-site maintenance.
- 100% tested.



UNE-EN 60335-2-58:1998+A1:99, UNE-EN 60335-1:1997, UNE-EN 55014-1:2002, UNE-EN 61000-2-3:2001; UNE-EN 61000-3-3:1997+C:99, UNE-EN 55014-2:1998

2006/95/EC, 2004/108/EC



Dishwasher P-50



TECHNICAL SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm
Maximum glass height: 330 mm

Cycle length: 180 "
Production baskets/hour: 20

Wash temperature: 0 °C - 65 °C
Rinse temperature: 0 °C - 90 °C

·Boiler capacity: 4.5 l
·Wash tank capacity: 26 l
·water consumption/cycle: 3 l
Loading

·Pump: 370 W / 0.5 Hp
·Tank: 2500 W
·Boiler: 2800 W
·Total loading: 3170 W

External dimensions

·Width: 600 mm
·Depth: 630 mm
·Height: 835 mm

Net weight: 63 Kg

DEFAULT EQUIPMENT

- Rinse aid doser.
- Variable detergent dosing equipment.
- 1 open basket.
- 1 mixed basket.
- 1 small cutlery basket.

OPTIONAL EQUIPMENT

- Drain pump with non-return valve.
- Stand.
- High feet kit 140-190mm.
- Stainless steel top-of tank filter set.