



Dishwasher P-100

2.5 KW WASH TANK AND 6 KW RINSE TANK

Commercial pass-through dishwasher with a useful height of up to 400 mm and 3 wash cycles with thermal cycle delay option included.

- A hood type dishwasher for both straight in line and corner situations -suitable for washing trays, as well as all types of plates, cups, glasses and cutlery.
- Professional washing with double system of rotating wash and rinse arms top and bottom.
- Hood operated, auto cycle star. 3 wash cycles.
- Manufactured from catering grade AISI 304 2B stainless steel and incorporating top quality components.
- The inside of the machine features rounded corners, the elimination of angles avoiding the accumulation of dirt.
- Precision positioned water jets guarantee optimum washing result for even the most stubbornly stained glasses. Easy to assemble, boltless rinse spray arms.
- A double filter system provides effective wash pump protection that is easily removed (for maintenance and cleaning)and replaced, without tools.
- A magnetic micro-switch stops the wash cycle, in the event of the hood being raised prematurely.
- Standard features include adjustable feet for levelling.
- A stainless steel, top of tank filter system is also included as standard.
- Rinse aid dosing equipment.
- Adjustable washing tank and boiler temperature and security in the boiler.
- Thermal cycle delay option, guaranteeing a minimum final rinse temperature of 85°C for each and every rinse cycle.
- Sammic ware washers are designed for easy and fast on-site maintenance.
- 100% tested.



UNE-EN 60335-2-58:1998+A1:99, UNE-EN 60335-1:1997, UNE-EN 55014-1:2002, UNE-EN 61000-2-3:2001, UNE-EN 61000-3-3:1997+C:99, UNE-EN 55014-2:1998

2006/95/EC, 2004/108/EC



Dishwasher P-100



TECHNICAL SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm
Maximum glass height: 400 mm

Cycles: 3
Cycle duration: 120 " / 180 " / 210 "
Production baskets/hour: 30 / 20 / 17
·Boiler capacity: 10 l
·Wash tank capacity: 40 l
·water consumption/cycle: 3.5 l
Loading

·Pump: 750 W / 1 Hp
·Tank: 2500 W
·Boiler: 6000 W
·Total loading: 6750 W

External dimensions

·Width:640 mm
·Depth: 756 mm
·Height: 1920 mm / 1468 mm

Net weight: 115 Kg

DEFAULT EQUIPMENT

- Rinse aid doser.
- 1 open basket.
- 1 mixed basket.
- 1 cutlery basket.

OPTIONAL EQUIPMENT

- Detergent dosing equipment.
- Version with drain pump and non-return valve available.