

# British Manufacturing since 1957



### The Professionals Choice

## 3001F

Counter-top, Automatic-Fill Water Boiler - with Filtration



#### **FULL SPECIFICATION**



### **3001F** Automatic Fill Water Boiler – With Filtration

Time	Countains Standard Dance
Type	Countertop - Standard Range
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	
Capacity (Litres)	17
Unit dimensions (W x D x H) mm	310 x 518 x 618 (depth includes drip-tray)
Packed dimensions (W x D x H) mm	425 x 590 x 775
Tap clearance mm	190mm
Product weight - empty (kg)	15
Product weight – full (kg)	36
Packed weight (kg)	18.5
CONSTRUCTION:	
Outer fabrication (body) construction	304 grade Stainless Steel (Superbrush polish)
Tank construction	304 & 316 grade Stainless Steel
Tank wall thickness	0.9mm
Drip-tray	304 grade Stainless Steel – (Mirror polish)
ELECTRICAL:	Total grade etaliness eteel (Will of polish)
	3
Power rating (kW)	230 V (50-60Hz)
Voltage supply	
Electrical supply	Single-phase, N & E (13A)
Plug type	UK standard 3-pin
Fitted cable length (m)	1.7m
PLUMBING:	
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4"BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	Front via drip-tray (or rear using kit not supplied)
PERFORMANCE:	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	42 mins (full tank capacity)
Output per hour (@ default temperature setting)	27 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	17 Litres
Recovery per minute	0.5 Litres
Stand-by power loss (idle mode)	0.09 kW/h
FILTRATION:	0.00 KW/II
	Voc
Multi-Filter (taste & odour, sediment & reduces lime-scale)	Yes
Filter Benefits	Latest triple-action; removes sediment & impurities such as
Mark Salar Parad Charles	chlorine and reduces limescale build-up
Mechanical sediment filtration	3 micron
Filter counter programmable	Yes (soft, medium & hard water settings)
OTHER FEATURES:	
Tank-baffle plates – unique design aids heat recovery &	Yes
reduces steam emissions to atmosphere	
Early warning lime-scale diagnostics (via LED light)	Yes – basic (from Jan 2015)
Dual safety protection	Yes - Over-boil & boil-dry protection
STANDARDS & APPROVALS:	
WRAS approved	Yes
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes (EN 60335-1 & 2)
WARRANTY & AFTER-SALES:	,
Guarantee	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)
opare parts, lillers & accessories	Jame day despaton (ii ordered belore spin)

Instanta Limited
T: 01704 501114
F: 01704 501115
E: sales@instanta.com





Certificate Numbers: FM01234 & EM01234