



# 1767-SK/III

## LOW TEMPERATURE SMOKER OVEN



• **HALO HEAT** . . . a controlled, uniform heat source that maintains close temperature tolerances throughout the cooking and holding function. Offers uniform and consistent cooking on a daily basis, low shrinkage of bulk or portion-cut protein items, higher food moisture content, and significantly longer holding life.



- Cooks, roasts, re-heats, smokes and holds in the same cabinet with set-and-forget controls to provide a better distribution of work loads.
- Smokes with real wood chips — no pressure cooking, no artificial smoke flavor.
- Smoke timer offers a choice of mild, medium, or heavy smoke flavor.
- Cold smokes fish and cheese.
- Cooks by time or by probe to sense internal product temperature and automatically converts from cook mode to hold mode once the set parameters have been reached.
- Eight programmable menu buttons store favorite recipes into memory (COOK/HOLD/TIME/PROBE SET-POINTS). Reduces operational requirements to simply loading the oven, pushing the power button, the preset menu button, and start.
- Clear, easy-to-read LED display indicates cook time remaining or the full range of programmed operating parameters.
- When cooking by probe, the oven maintains a record of the highest and lowest temperatures sensed by the food probe to assure foods are cooked to the temperature required.
- Oven includes the patented SureTemp™ heat recovery system to assure immediate compensation for any heat loss whenever the door is opened and provides an audible reminder if the door has been left open for more than three minutes.
- Antimicrobial handles retard the growth of illness-causing pathogens.

Two (2) individually controlled smoker compartments enclosed in one 20 gauge stainless steel exterior cabinet. Each door is furnished with a magnetic door latch. Each compartment is equipped with two (2) stainless steel side racks with eleven (11) pan positions spaced on 1-3/18" (35mm) centers, two (2) stainless steel wire shelves, one (1) stainless steel Rib Rack, and one (1) stainless steel drip pan with drain. Oven is furnished with an exterior, front mounted stainless steel drip tray and one (1) sample bag each of cherry, hickory, apple & maple wood chips. Oven includes one (1) set of 5" (127mm) casters — 2 rigid, and 2 swivel with brake.

A single Deluxe control includes individual settings for upper and lower cavity and consists of a 4 digit L.E.D. display, ON/OFF key for each compartment; cook temperature key with an adjustable cook range from 200°F to 325°F (93°C to 162°C); time control key with set-points from 1 minute to 24 hours; smoke time control key with set-points from 1 minute to 1 hour; probe control key with adjustable set-points between 50°F and 195°F (10°C to 91°C); and hold temperature key with an adjustable hold range from 60°F to 205°F (15°C to 96°C). Control includes eight (8) programmable menu keys with locking capability along with the ability to set individual cook and hold parameters; hold mode count-up timer, indicator lights for operation status; and start key. The control has a built-in lock out feature and is equipped with a voltage conversion feature to match the line voltage provided by the electric power supplier.


☐ **MODEL 1767-SK/III:** Double compartment low temperature smoker oven with Deluxe control.

### FACTORY INSTALLED OPTIONS

- Specify Door:
  - ☐ Solid Door, standard
  - ☐ Window Door, optional
- Specify Door Swing:
  - ☐ Right-hand swing, standard
  - ☐ Left-hand swing, optional
- Specify Voltage:
  - ☐ 208-240
  - ☐ 230
- Specify exterior panel color:
  - ☐ Stainless steel, standard
  - ☐ Burgundy, optional
  - ☐ Custom, optional
- Cooking thermostat limit set at 250°F for restricted areas of the U.S.A.
- ☐ Specify on order as required.

### ADDITIONAL FEATURES

- ☐ **Rib Rack Shelf • Item SH-2743**  
Special non-magnetic stainless steel wire shelf designed to hold ribs or fish in an upright position for more even smoking. Each shelf will hold thirteen full ribs. One (1) Rib Rack Shelf is furnished with each smoker. Additional racks are available as an option. Total oven capacity: Two (2) Rib Rack Shelves.



## Lifetime Warranty

On all Cook & Hold heating elements (EXCLUDES LABOR).



ANSI/NSF 4



## HALO HEAT®

W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A.


PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA

FAX: 262.251.7067 800.329.8744 U.S.A. ONLY

[www.alto-shaam.com](http://www.alto-shaam.com)


# 1767-SK/III

## LOW TEMPERATURE SMOKER OVEN



\*60-11/16\" (1540mm) - with optional 3-1/2\" (89mm) casters  
 \*62-1/8\" (1577mm) - with optional 6\" (152mm) legs

### DIMENSIONS: H x W x D

#### EXTERIOR:

61-15/16\" x 25-11/16\" x 32-3/4\"  
 (1572mm x 651mm x 832mm)

#### INTERIOR: (EACH COMPARTMENT)

20-1/16\" x 22\" x 26-1/2\"  
 (510mm x 559mm x 673mm)

### ELECTRICAL

VOLTAGE	PHASE	CYCLE/HZ	AMPS	kW	CORD & PLUG
208-240 (AGCY)	1	60	32.0	7.7	NO CORD
at 208	1	60	31.0	6.5	OR PLUG
at 240	1	60	35.8	8.6	
230	1	50	29.1	6.1	NO CORD OR PLUG

### PRODUCT/PAN CAPACITY (PER COMPARTMENT)

100 lb (45 kg) MAXIMUM

VOLUME MAXIMUM: 53 QUARTS (67 LITERS)

	FULL-SIZE PANS	GASTRONORM 1/1:
Nine (9)	20\" x 12\" x 2-1/2\"	(530mm x 325mm x 65mm)
Seven (7)	20\" x 12\" x 4\"	(530mm x 325mm x 100mm)

#### FULL-SIZE SHEET PANS:

Up to Five (5)\* 18\" x 26\" x 1\" on wire shelves only

\*ADDITIONAL SHELVES REQUIRED

### CLEARANCE REQUIREMENTS

18\" (457mm) minimum clearance at the back from heat producing equipment. To protect the electronic control, maintain sufficient side clearance to prevent the control area from reaching any temperature at or above 140°F (60°C).

### WEIGHT

NET: 359 lb (163 kg) EST. SHIP: 450 lb (204 kg)

### CARTON DIMENSIONS: (L x W x H)

35\" x 35\" x 82\" (889mm x 889mm x 2083mm)

### INSTALLATION REQUIREMENTS

- Oven must be installed level.
- The oven must not be installed in any area where it may be affected by steam, grease, dripping water, extreme temperatures, or any other severely adverse conditions.
- Appliances with casters and no cord or plug must be secured to the building structure with a flexible connector. NOT FACTORY SUPPLIED.

### OPTIONS & ACCESSORIES

<input type="checkbox"/> Bumper, Full-perimeter	5010371	<input type="checkbox"/> Pan Grid, Wire - 18\" x 26\" PAN INSERT	PN-2115
<input type="checkbox"/> Carving Holder, Prime Rib	HL-2635	<input type="checkbox"/> Security Panel with Lock	5013936
<input type="checkbox"/> Carving Holder, Steamship (Cafeteria) Round	4459	<input type="checkbox"/> Shelf, Stainless Steel, Flat Wire	SH-2324
Casters, Stem - 2 RIGID, 2 SWIVEL W/ BRAKE		<input type="checkbox"/> Shelf, Stainless Steel, Rib Rack	SH-2743
<input type="checkbox"/> 3-1/2\" (89mm)	5008017	Wood Chips bulk pack - 20 lb (9 kg)	
<input type="checkbox"/> Door Lock with Key - EACH HANDLE	LK-22567	<input type="checkbox"/> Apple	WC-22543
<input type="checkbox"/> Drip Pan with Drain	14831	<input type="checkbox"/> Cherry	WC-22541
<input type="checkbox"/> Legs, 6\" (152mm), Stemmed (SET OF FOUR)	5011149	<input type="checkbox"/> Hickory	WC-2829
		<input type="checkbox"/> Maple	WC-22545