





Dual Fuel Ranges 900mm wide

OD8007

- 7.5kW dual concentric burners for focused heat distribution from a fast boil to a low simmer
- Individual heavy-duty single cast iron supports, built to withstand the rigours of the busiest kitchen
- Low flue to allow use of the complete hob top
- 6kW, fan assisted oven
- Large capacity oven 6 x GN1/1
- Double insulated doors and side panels for safe operation, efficiency and economy



Hob Top Features

- 6 x 7.5kW dual-concentric burners
- Individual heavy-duty single cast iron pan supports with extended pan support fingers
- Flame failure protection
- Stainless steel spill trays
- Low flue to allow complete use of hob top

Oven features

- 6kW heating element
- Precise thermostatic control from 50 °C to 250 °C
- Twin fan assisted oven
- Power to the appliance indicator light (green)
- Oven has reached desired temperature indicator light (amber)
- 180° side hinged doors
- Oven capacity 6 x GN1/1
- Heavy-duty easy remove wire chrome rack supports
- 5 position racking with anti tilt guards and safety stops

Cleaning and Servicing

- Easy clean stainless steel external finish
- Removable stainless steel spill trays
- Heavy-duty easy remove wire chrome rack supports
- Stainless steel oven lining with removable side and base liner
- Access to all parts from the front and top of unit

Overall construction

- Permanent laser etched markings on fascia and knobs
- Fully framed 1.2mm steel chassis
- 1.2 mm stainless steel base panel
- 0.8 mm stainless steel side panels
- Castors as standard
- Sits flush to the wall, recess for services

Hob top construction

• 1.2 mm stainless steel welded bull nose and hob surround

Oven construction

- 0.8 mm stainless steel outer door skin
- Reinforced door seal
- Double insulated doors, side panels
- Stainless steel oven liner

Inclusive Accessories

• 3 chrome plated shelves

Available Options

- Adjustable legs
- /N Natural or /P propane gas


Available Accessories

OA8902 splashback/shelf




Technical Data

| | OD8007 |
|--|----------------------------------|
| Width (mm) | 900 |
| Depth (mm) | 800 |
| Overall height (mm) | 913 |
| Hob height (mm) | 900 |
| Usable oven capacity H x W x D (mm) | 419 x 770 x 530 |
| Oven shelf size W x D (mm) | 770 x 530 |
| Hob | 6 open burners |
| Heat input per hob burner (kW) | 7.5 natural, 6.7 propane |
| Total heat input at full rate (kW) | 45 natural, 40.2 propane |
| Total heat input at full rate (Btu per hour) | 153,546 natural, 137,168 propane |
| Gas consumption at full rate Natural (m3 h-1) | 4.29 |
| Gas consumption at full rate Propane (kg h-1) | 2.87 |
| Gas pressure (mbar) | 20 natural, 37 propane |
| Gas connection (BSP) | 3/4" |
| Oven rating (kW) | 6.0 |
| Total electrical power rating (kW) | 6.0 |
| Electrical supply 1N~+E 230V 50-60Hz Current Rating (Amps) | 26.4 |
| Electrical supply 3N~+E 400V 50-60Hz Current Rating (Amps) | L1 = 9.0 L2 = 8.7 L3 = 8.7 |
| Net weight (kg) | 164 |
| Packed weight (kg) | 178 |
| Shipping volume (m3) | 1.2 |
| IPX | IPX4 |











© UK General Tel: 01522 875555



WK Sales e-mail: sales@lincat.co.uk

■ International Sales Tel: +44 1522 503250
■ International Sales e-mail: export@lincat.co.uk







