



DYNAMIC PREPARATION

COMMERCIAL POTATO PEELERS



Potato Peeler M-5

5 KG. / 11 POUNDS LOAD PER CYCLE.

Commercial stainless steel construction potato peeler suitable for reduced space areas.

Also suitable to peel carrots and other similar products.

- · Abrasive peeling. The abrasive is highly resistant and long lasting.
- · Base Plate lined with highly resistant and long lasting abrasive.
- · Stainless steel body.
- · Ideal for placement near sink for drainage
- · Very easy to install
- · Water inlet system with non-return air break.
- · Integral control panel complete with on/off push buttons and a 0-6 minute timer.
- · Optional extra: A stainless steel stand complete with removable filter chamber.

TECHNICAL SPECIFICATIONS

Hourly production: 80 Kg / 100 Kg Capacity per load: 5 Kg Timer (min-max): 0 ' - 6 ' Total loading: 300 W Noise level (1m.): 70 dB(A) Background noise:32 dB(A)

External dimensions (WxDxH)

·Width: 333 mm ·Depth: 367 mm ·Height: 490 mm

External dimensions with stand

·Width with stand: 425 mm ·Depth with stand: 555 mm ·Height with stand: 965 mm

Plate speed: 300 rpm

Net weight: 15 Kg

DEFAULT EQUIPMENT

OPTIONAL EQUIPMENT

· Stainless steel floor stand.

· Filter with no-foam feature.





SAMMIC, S.L. Basarte, 1 · 20720 AZKOITIA www.sammic.com

2006/95/EC, 2004/108/EC.

UNE-EN 60335-2-64:2001, UNE-EN 60335-1:1997 UNE-EN 55014-1:2002+A1:02, UNE-EN 61000-3-2:01 UNE-EN 61000-3-3:97+A1:02+C:99, UNE-EN 55014-2:98+A1:02