



Dishwasher X-80

500X500MM RACKS. MAX. LOADING HEIGHT: 400MM.

Commercial dishwasher with tall base that allows more comfortable operation.

Commercial dishwasher tall base with a max. loading height of 400mm. to facilitate the washing of trays.
With easy-to-use electronic panel complete with wash and rinse temperature display.
This machine includes stainless steel top-of-tank filters.

- For washing all type of plates, glasses, cups and cutlery.
- Washing with double system of rotating dispersers (top and bottom)
- 3 wash cycles.
- Manufactured from catering grade AISI 304 2B stainless steel and incorporating top quality components.
- Easy to use electronic control panel with anti-moisture seal and wash & rinse tank temperature displays.
- Double skinned door with high efficiency seal, ensuring thermal and acoustic insulation. Magnetic door micro-switch.
- Removable stainless steel rack holders ensure even distribution of wash water without dead zones. Precision positioned water jets guarantee optimum washing result for even the most stubbornly stained glasses. Easy to assemble, boltless rinse spray arms.
- A double filter system provides effective wash pump protection that is easily removed (for maintenance and cleaning) and replaced, without tools.
- Inside of the machine with rounded finished: absence of angles avoiding the accumulation of dirt.
- Completely rounded, stainless steel wire rack support and guide.
- A stainless steel, top-of-tank filter system is also included as a standard.
- Automatic detergent and rinse aid dosing equipment.
- Wash tank and rinse boiler temperature adjustment and a thermal cycle delay option, guaranteeing a minimum final rinse temperature of 85°C for each and every rinse cycle.
- Sammic ware washers are designed for easy and fast on-site maintenance.
- 100% tested.



SAMMIC, S.L.
Basarile, 1 · 20720 AZKOITIA
www.sammic.com

2006/95/EC, 2004/108/EC

UNE-EN 60335-2-58:1998+A1:99, UNE-EN 60335-1:1997
UNE-EN 55014-1:2002, UNE-EN 61000-2-3:2001
UNE-EN 61000-3-3:1997+C:99, UNE-EN 55014-2:1998



Dishwasher X-80



TECHNICAL SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm
Maximum glass height: 400 mm

Cycle duration: 120 " / 150 " / 210 "
Production baskets/hour: 30 / 24 / 17

Wash temperature: 0 °C - 65 °C
Rinse temperature: 0 °C - 90 °C
·Boiler capacity: 10 l
·Wash tank capacity: 26 l
·water consumption/cycle: 2.9 l
Loading

·Pump: 730 W / 1 Hp
·Tank: 2500 W
·Boiler: 6000 W
·Total loading: 6730 W

External dimensions (WxDxH)

·Width: 620 mm
·Depth: 630 mm
·Height: 1320 mm

Net weight: 78 Kg
Noise level (1m.): <70 dB(A)

DEFAULT EQUIPMENT

- Rinse aid pump.
- Detergent dosing equipment.
- Stainless steel top-of-tank filter set.
- 1 open basket.
- 1 plate basket.
- 1 small cutlery basket.

OPTIONAL EQUIPMENT

- Model with drain pump and non-return valve.