



PASSTHROUGH DISHWASHERS

The Ecomax range of passthrough dishwashers (also known as hood types) is efficient and economical. Perfectly suited to any busy kitchen, the robust, high quality range is sure to meet your operational requirements.

ECOMAX H602/S VERSUS ECOMAX PLUS H603/S

RACKS PER HOUR



LOADING HEIGHT



CYCLE TIME (secs)



WATER CONSUMPTION per cycle



Turn over for full machine specs.

SPECIFICATIONS

GENERAL

DIMENSIONS

Height hood open

Width with handle

Number of racks

Loading height

Rack size

Max pints/plates per rack

Max racks p/h

New weight (kg)

Rinse booster pump

Built in detergent dispenser

Built in rinse aid dispenser

CONTROLS

Class A air gap

Thermostop control

Programme times. secs

Water consumption/cycle

Wash tank capacity

Wash tank heating

Rinse tank capacity

Drain pump

Wash pump rating

Wash pump flow rate

Rinse pump rating

WATER

Integral softener

Water pressure

Water temp

ELECTRIC

Voltage 3P

Voltage 1P

Total loading 3P

Total loading 1P

ECOMAX

H602/S

635mm(w)

740mm (d)

1960mm(h)

715mm

1 x plate rack,
1 x cutlery basket

440mm

500 x 500mm

18

48

100

YES

YES

YES

ELECTRONIC

YES

YES

75 - 150

2.8L

21L

2.5kW

5.6L

YES

0.4kW

225L/min

0.27kW

YES

0.8 – 6 BAR

MAX 60°C

400/50/3

230/50/1

3 x 16A/6.6kW (Factory setting)

25A/4.9kW

ECOMAX PLUS

H603/S

635mm (w)

740mm(d)

1960mm (h)

715mm

1 x plate rack,
1 x open rack,
1 x cutlery basket

440mm

500 x 500mm

18

60

105

YES

YES

YES

ELECTRONIC

YES

YES

60 - 90

2.5L

21L

2.5kW

5.6L

YES

0.7kW

400L/min

0.1kW

YES

0.8 – 6 BAR

MAX 60°C

400/50/3

230/50/1

3 x 16A/7.0kW (Factory setting)

25A/4.9kW



ECOMAX H602/S



ECOMAX PLUS H603/S

Tabling not included.

Technical details may be subject to change at any time without prior notice.

HOBART INDEPENDENT

Southgate Way, Orton Southgate,
Peterborough, PE2 6GN

0870 168 8881

or visit www.hobartindependent.co.uk



UNDERCOUNTER DISHWASHERS

A range of high performance commercial dishwashers, designed to deliver consistently clean results. With controls to ensure easy operation and additional features to guarantee economical usage and quieter operation, the Ecomax range of undercounter dishwashers delivers consistent, sparkling results.

ECOMAX F502/S VERSUS ECOMAX PLUS F503/S

RACKS PER HOUR



LOADING HEIGHT



CYCLE TIME (secs)



WATER CONSUMPTION per cycle



DOUBLE SKINNED CONSTRUCTION



Turn over for full machine specs.

SPECIFICATIONS

GENERAL

DIMENSIONS

Depth Door Open

Number of racks

Loading height

Rack size

Max pints/plates per rack

Max racks p/h

New weight (kg)

Rinse booster pump

Built in detergent dispenser

Built in rinse aid dispenser

Double skinned construction

CONTROLS

Class A air gap

Thermostop control

Programme times. secs

Water consumption/cycle

Wash tank capacity

Wash tank heating

Rinse tank capacity

Drain pump

Wash pump rating

Wash pump flow rate

Rinse pump rating

WATER

Integral softener

Water pressure

Water temp

ELECTRIC

Voltage 3P

Voltage 1P

Total loading 3P

Total loading 1P

ECOMAX

F502/S

575mm(w)

600mm(d)

830mm(h)

1046mm

1 x plate rack,
1 x cutlery basket

355mm

500 x 500mm

18

60

44

YES

YES

YES

DOOR

ELECTRONIC

YES

YES

60 – 180

2.9L

25L

2.0kW

5.6L

YES

0.37kW

220L/min

0.25kW

YES

0.8 – 6 BAR

MAX 60°C

400/50/3

230/50/1

3 x 16A/6.0kW

25A/4.2kW(Factory setting)

13A/2.3kW

ECOMAX PLUS

F503/S

600mm(w)

600mm (d)

820mm(h)

1046mm

1 x plate rack,
1 x open rack,
1 x cutlery basket

425mm

500 x 500mm

18

40

60

YES

YES

YES

FULL

ELECTRONIC

YES

YES

90 – 180

2.5L

10.6L

0.8kW

6.8L

YES

0.6kW

200L/min

0.1kW

YES

0.8 – 6 BAR

MAX 60°C

400/50/3

230/50/1

3 x 16A/7.7kW

25A/5.6kW (Factory setting)

13A/2.8kW



ECOMAX F502/S



ECOMAX PLUS F503/S

Technical details may be subject to change at any time without prior notice.

HOBART INDEPENDENT

Southgate Way, Orton Southgate,
Peterborough, PE2 6GN

0870 168 8881

or visit www.hobartindependent.co.uk



GLASSWASHERS

Our research indicates that 94% of customers would be put off going to an outlet again if confronted with dirty glassware. Ecomax glasswashers make it quick, simple and cost effective to deliver a high quality finish, every time.

ECOMAX G502 VERSUS ECOMAX PLUS G503/S

RACKS PER HOUR



MAX GLASS CLEARANCE HEIGHT



CYCLE TIME (secs)



WATER CONSUMPTION per cycle



DOUBLE SKINNED CONSTRUCTION



Turn over for full machine specs.

SPECIFICATIONS

GENERAL

DIMENSIONS

Max Glass Clearance Height

Depth Door Open

Number of racks

Rack size

Max pints/plates per rack

Max racks p/h

New weight (kg)

Rinse booster pump

Built in detergent dispenser

Built in rinse aid dispenser

Double skinned construction

CONTROLS

Class A air gap

Thermostop control

Programme times. secs

Water consumption/cycle

Wash tank capacity

Wash tank heating

Rinse tank capacity

Drain pump

Wash pump rating

Wash pump flow rate

Rinse pump rating

WATER

Integral softener

Water pressure

Water temp

ELECTRIC

Voltage 3P

Voltage 1P

Total loading 3P

Total loading 1P

ECOMAX

G502

575mm(w)

600mm(d)

830mm(h)

355mm

1046mm

1 x 4 division glass rack

500 x 500mm

20

60

64

NO

YES

YES

DOOR

ELECTRONIC

NO

YES

60 – 180

2.9L

25L

2.0kW

5.6L

YES

0.37kW

220L/min

0.25kW

NO

2 – 6 BAR

N/A

400/50/3

230/50/1

3 x 16A/6.0kW

25A/4.2kW(Factory setting)

13A/2.3kW

ECOMAX PLUS

G503/S

600mm(w)

600mm(d)

820mm(h)

425mm

1046mm

1 x 5 division glass rack

500 x 530mm

25

40

60

YES

YES

YES

FULL

ELECTRONIC

YES

YES

90 – 120

2.5L

10.6L

0.8kW

6.8L

YES

0.6kW

200L/min

0.1kW

YES

0.8 – 6 BAR

MAX 60°C

400/50/3

230/50/1

3 x 16A/7.7kW

25A/5.6kW(Factory setting)

13A/2.8kW



ECOMAX G502



ECOMAX PLUS G503/S

Technical details may be subject to change at any time without prior notice.

HOBART INDEPENDENT

Southgate Way, Orton Southgate,
Peterborough, PE2 6GN

0870 168 8881

or visit www.hobartindependent.co.uk



COMPACT GLASSWASHERS

Our research indicates that 94% of customers would be put off going to an outlet again if confronted with dirty glassware. Ecomax glasswashers make it quick, simple and cost effective to deliver a high quality finish, every time.

ECOMAX G402 VERSUS ECOMAX PLUS G403/S

RACKS PER HOUR



MAX GLASS CLEARANCE HEIGHT



CYCLE TIME (secs)



WATER CONSUMPTION per cycle



DOUBLE SKINNED CONSTRUCTION



Turn over for full machine specs.

SPECIFICATIONS

GENERAL

DIMENSIONS

Max Glass Clearance Height

Depth Door Open

Number of racks

Rack size

Max pints/plates per rack

Max racks p/h

New weight (kg)

Rinse booster pump

Built in detergent dispenser

Built in rinse aid dispenser

Double skinned construction

CONTROLS

Class A air gap

Thermostop control

Programme times. secs

Water consumption/cycle

Wash tank capacity

Wash tank heating

Rinse tank capacity

Drain pump

Wash pump rating

Wash pump flow rate

Rinse pump rating

WATER

Integral softener

Water pressure

Water temp

ELECTRIC

Voltage 3P

Voltage 1P

Total loading 3P

Total loading 1P

ECOMAX

G402

435mm(w)

530mm(d)

700mm(h)

300mm

866mm

1 x 4 division glass rack

385 x 385mm

16

40

44

NO

YES

YES

DOOR

ELECTRONIC

NO

YES

90 – 120

2.5L

11L

2.0kW

4.9L

YES

0.25kW

150L/min

0.25kW

NO

2 – 6 BAR

N/A

400/50/3

230/50/1

3 x 16A/5.9kW

13A/2.2kW (Factory setting)

20A/4kW

ECOMAX PLUS

G403/S

460mm(w)

590mm(d)

700mm(h)

315mm

943mm

1 x 4 division glass rack

400 x 400mm

16

40

50

YES

YES

YES

FULL

ELECTRONIC

YES

YES

90 – 180

2.5L

8L

0.8kW

4L

YES

0.6kW

200L/min

0.1kW

YES

0.8 – 6 BAR

MAX 60°C

400/50/3

230/50/1

3 x 16A/5.4kW

13A/2.7kW(Factory setting)

20A/4.0kW



ECOMAX G402



ECOMAX PLUS G403/S

Technical details may be subject to change at any time without prior notice.

HOBART INDEPENDENT

Southgate Way, Orton Southgate,
Peterborough, PE2 6GN

0870 168 8881

or visit www.hobartindependent.co.uk

RACK CONVEYOR DISHWASHERS

The Ecomax Plus rack conveyors are truly outstanding in their field, delivering ease of use and low running costs. Designed for higher volume operations, the machines ensure a gleaming finish without fail.



ECOMAX PLUS C803A

- Wash up to 110 racks per hour (1,980 plates)
- Compact design – just 1350mm in length
- Stainless steel wash arms with anti-block jets
- Optional dryer and heat recovery available

Turn over for full machine specs.

ECOMAX PLUS C803EA

- Effective pre-wash feature for optimal wash results
- Large wash capacity – wash up to 140 racks per hour (2,520 plates)
- Stainless steel wash arms with anti-block jets
- Optional dryer and heat recovery available

SPECIFICATIONS

GENERAL

DIMENSIONS

Number of racks/hr

Rack size

Racks supplied

Max plates per rack

Rinse booster pump

CONTROLS

Class A air gap

Rinse water consumption

Pre-wash tank capacity

Wash tank capacity

Wash tank heating

Pre-wash pump rating

Pre-wash pump flow rate

Wash pump rating

Wash pump flow rate

Noise level

Dryer

Drying tunnel length

Drying tunnel loading

Heat recovery

Circulation

Reduction in kW loading

WATER

Water flow pressure

ELECTRIC

Total connected load

(water fed @ 40°C)

Total connected load

(water fed @ 10°C)

DRAIN

Drain size(diameter in inches)

Max height above floor level

ECOMAX PLUS

C803A

1350mm(w)

785mm(d)

1961mm(h)

110

500 x 500mm

1 x plate rack

1 x cup rack

1 x cutlery basket

18

YES

ELECTRONIC

YES

230ltrs/hr

-

105ltrs

12kW

-

-

1.5kW

350 ltrs/min

64dB

Optional

650mm

3.5kW

Optional

800m3/hr

6kW

1.5 – 6 BAR

1.5 – 6 BAR

26.8kW

26.8kW

35.8kW

35.8kW

50mm

185mm

ECOMAX PLUS

C803EA (PRE-WASH)

1850mm(w)

785mm(d)

1961mm(h)

140

500 x 500mm

1 x plate rack

1 x cup rack

1 x cutlery basket

18

YES

ELECTRONIC

YES

240ltrs/hr

10ltrs

105ltrs

12kW

0.27kW

20ltrs/min

1.5kW

350 ltrs/min

64dB

Optional

650mm

3.5kW

Optional

800m3/hr

6kW

1.5 – 6 BAR

1.5 – 6 BAR

26.9kW

26.9kW

35.9kW

35.9kW

50mm

185mm



ECOMAX PLUS C803A



ECOMAX PLUS C803EA

Tabling not included.

Technical details may be subject to change at any time without prior notice.

HOBART INDEPENDENT

Southgate Way, Orton Southgate,
Peterborough, PE2 6GN

0870 168 8881

or visit www.hobartindependent.co.uk