



PLATINUM



FREESTANDING PLATINUM FREEZER SOLID DOOR 400L WHITE



- ✓ **Large 400L Capacity**
offers maximum frozen storage space
- ✓ **-18°C to -25°C Temperature Range**
allows user to select ideal temperature
- ✓ **6 Fixed Height Shelves**
for effective stock control
- ✓ **Stylish Integrated Handle**
for ease of opening
- ✓ **4 Fitted Castors**
with two locking at front for ease of movement
- ✓ **Lockable**
- ✓ **Replaceable Door Seal**
- ✓ **Self Closing Door**
means door cannot be left open accidentally,
spilling contents
- ✓ **Manual Defrost**
for low on-going maintenance
- ✓ **Warning Alarms**
high/low temperature and door open alarms to
alert users to a problem

SKU CODE: PRODUCT CODE: DESCRIPTION:

444441144 CFS400W

Freestanding Platinum Freezer Solid Door 400L White



FULL SPECIFICATION – CFS400W FREESTANDING PLATINUM FREEZER SOLID DOOR 400L WHITE

Description	Freestanding
SKU Code	444441144
EAN Code	5052263011441
GDPA Code	CFS400W
Unit External Width (mm)	603
Unit External Depth (mm)	653
Unit External Height (mm)	1960
Packed Width (mm)	665
Packed Depth (mm)	715
Packed Height (mm)	1985
Product Weight (kg)	85
Packed Weight (kg)	101
Internal Dimensions (mm) (WxDxH)	480x448x1623
Gross Capacity (L)	400
Net Capacity (L)	349
Material - Exterior Finish	White Painted Steel
Material - Interior Finish	Plastic (HIPS/ABS Mix)
Stackable	No
Gastronorm Compatible	-
Colour	White
Internal Temperature Range	-18°C to -25°C
Maximum Ambient Operating Temperature	Up to 38°C
Defrost Type	Manual
Forced Air Cooling (Fan)	Yes
Door Type	Solid
Door Style	Hinged, reversible
Self Closing Door	Yes
Door Open Depth (mm)	1220
Replacement Door Seal	Yes
Controller type	Electronic
Open Door Sensor/Alarm	Yes
Hi/Low Temperature Alarm	Yes
External Temperature Display	Yes
Rollers/Castors	4 fitted castors (2 lockable fronts)
Number of Shelves	6
Number of Shelf Positions	Fixed
Shelf Size (mm) (WxD)	422 x 410
Shelf Material	Painted Aluminium
Internal LED Light	No
Light Activation	-
Fitted Lock	Yes
Insulation Thickness (mm)	58
Insulation Material	Pentane
Voltage Supply	220/240v
Power Rating (kW)	0.22
Supplied with Fitted UK Plug	Yes
Fitted Cable Length (m)	1.8
Refrigerant Type	R134a
CFC Free	Yes
HFC Free	No
HCFC Free	Yes
Ammonia Free	Yes
Heat Rejection (Watts)	300
Energy Consumption (Kw/h) (24hrs)	2.4