

HOOD TYPE DISHWASHER 900

Bar Aid
German engineered for market-leading quality
by **HOBART**



With renowned German engineering, the Bar Aid range from Hobart delivers market-leading quality at really competitive prices. Offering exceptional wash results, unquestionable reliability and low running costs, Bar Aid is the ideal and convenient solution to your dishwashing needs, available exclusively through the dealer network.

You need...

- ✓ User friendly...
- ✓ Good hygiene standards...
- ✓ Energy saving...
- ✓ Outstanding results...
- ✓ Optimum water quality...
- ✓ Fast performance...
- ✓ Streak free...
- ✓ Cost efficient...
- ✓ Perfect rinsing...
- ✓ Choice of wash cycles...

Bar Aid delivers...

single button control with colour cycle indication – easy to use and understand

hygienic self flushing cycle on shut down with two stage strainer to remove debris

enclosed hood allows for double racking and prevents heat and steam escaping

powerful pump delivers total wash coverage via separate upper and lower wash and rinse arms

optional built-in water softener ensures the finest water quality to deliver a sparkling finish

capable of up to 60 rack per hour (approx. 240 covers)

integral detergent and rinse aid pumps deliver precise dosing saves on water, energy and detergent

advanced rinse system delivers optimised water distribution

choice of 60, 90 or 120 second cycles to suit variety of ware and degree of soiling

Tel: 0870 168 8881

www.hobartindependent.co.uk

HOOD TYPE DISHWASHER 900

SPECIFICATIONS

| General | 900 |
|------------------------------|---|
| Dimensions | 635mm(w) 740mm(d) 1510mm(h) |
| Height hood open | 1995mm |
| Width with handle | 758mm |
| Number of racks | 1 x plate rack, 1 x open rack, 1 x cutlery basket |
| Rack size | 500 x 500mm |
| Max pints/plates per rack | 18 |
| Max racks p/h | 60 |
| New Weight (kg) | 105 |
| Rinse booster pump | YES |
| Built in detergent dispenser | YES |
| Built in rinse aid dispenser | YES |
| Double skinned door | YES |
| Controls | ELECTRONIC |
| Class A air gap | YES |
| Thermostop Control | YES |
| Programme times. secs | 60, 90, 120 |
| Water consumption/cycle | 2.5L |
| Wash tank capacity | 21L |
| Wash tank heating | 2.5kW |
| Rinse tank capacity | 5.6L |
| Drain pump | YES |
| Wash pump rating | 0.7kW |
| Wash pump flow rate | 400L/min |
| Rinse pump rating | 0.1kW |
| Rinse pump flow rate | 115L/min |
| Noise level (dB) | 65 |
| Water | |
| Water pressure | 0.8 – 6 BAR |
| Water temp | MAX 60°C |
| Electric | |
| Voltage 3P | 400/50/3 |
| Voltage 1P | 230/50/1 |
| Total loading 3P | 3 x 16A/7.0kW (default) |
| Total loading 1P | 25A/4.9kW |



Technical details may be subject to change at any time without prior notice.

HOBART INDEPENDENT

Southgate Way, Orton Southgate,
Peterborough PE2 6GN

0870 168 8881

or visit www.hobartindependent.co.uk

Bar Aid
German engineered for market-leading quality
by **HOBART**