



# Product Code: MBCT100

## Floorless Modular Blast Chiller with 700mm door width

---



### Features & Benefits

---

- MBCT models are supplied floorless for blast chilling application only
- 100kg chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Freezing capacity from 70° to -18°C in less than 240 minutes within specifications
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status.
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Operator-friendly fans cut-out whenever door is opened
- HACCP software is available as an option in 3 formats for data retrieval and management

Shelving

|   |          |
|---|----------|
| Additional S/S Trayslides                 | Standard |
| Trolley - Gastronorm - 1/1 (Not Supplied) | Option   |
| Trolley - Gastronorm - 2/1 (Not Supplied) | Option   |
| Trolley Capacity - 690x1040x1890          | Standard |

Refrigeration

|                           |          |
|---------------------------|----------|
| R404a - Industry Standard | Standard |
| Less Condensing Unit      | Standard |

Specification

|   |          |
|---|----------|
| Blast Chiller                           | Standard |
| Width                                   | 1350     |
| Depth                                   | 1330     |
| Height                                  | 2350     |
| Weight (Unpacked, kg)                   | 790      |
| Weight (Packed, kg)                     | 790      |
| Chilling Capacity (Kgs)                 | 100      |
| Gross Volume (Ltr)                      | 100      |
| RS485 connection for HACCP data logging | Option   |

Base Fittings

|                             |          |
|-----------------------------|----------|
| Remote Refrigeration System | Standard |
|-----------------------------|----------|

Electrical & Service Data

|          |          |
|----------|----------|
| 230/50/1 | Standard |
|----------|----------|

Finish

|   |          |
|---|----------|
| White lam ext and door & white control panel              | Standard |
| White lam int & ext, 304 s/s door and white control panel | Option   |
| 304 s/s   | Option   |

Doors

|                       |          |
|-----------------------|----------|
| Solid                 | Standard |
| Left Hand Hinged Door | Option   |

Product Extras

|               |        |
|---------------|--------|
| Hold Facility | Option |
|---------------|--------|

Footnotes

- MBC models are supplied floorless for blast chilling application only.
- Control panel sprayed white
- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15oC e.g. Prep rooms
- Condensing Unit: All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral).



Energy



Quality



Value



Design



Hygiene



After Care