

www.burco.co.uk



BURCO 20L COUNTERTOP AUTO FILL WATER BOILER - With Filtration





- Easy-to-replace internal filtration system
 Inhibits limescale build-up and other impurities to prolong the life of the appliance and provide the best tasting beverage.
- Extra Large 20L tank capacity
 Ideal for premises requiring a large volume of instant hot water.
- ✓ Manufactured in the UK
- Advanced LCD touch control screen
 Provides great user functionality and the advanced diagnostics alert the user when the filter cartridge needs to be replaced.
- Variable water temperature range
 Simply select your preferred setting between 80°C and 98°C.
- Energy saving "Eco" Mode Reduces running costs.
- Powerful 2.8kW heating element
 For rapid heat-up time.
- Comes with up to 2 years parts and labour warranty
- ✓ WRAS Approved

DESCRIPTION:



SKU CODE: PRODUCT CODE:

444442464 BC PLS AF CT 20L 3KW UK

Burco 20L Countertop Auto Fill Water Boiler – with filtration

BURCO

www.burco.co.uk





FULL SPECIFICATION - Burco 20L Countertop Auto Fill Water Boiler – with filtration

SKU code	44442464
GDPA code	BC PLS AF CT 20L 3KW UK
EAN code	5052263024649
Туре	Countertop
Capacity (L)	20
Unit dimensions (W x D x H) (mm)	344 x 464 x 689 (depth includes tap & drip tray)
Packed dimensions (W x D x H) (mm)	450 x 550 x 760
Product weight (kg)	11.4
Packed weight (kg)	14.43
Body construction	430 grade Stainless Steel
Tank construction	304 grade Stainless Steel
Drip tray size (W x D x H) (mm)	345 x 220 x 92
Trim & drip tray plastic type	ABS
Power rating (kW)	3
Water delivery temperature	80°C - 98°C
Typical Heating and Cooling times	Heat up time to 98°C: 56 minutes
	Heat from 80-98°C: 12 minutes
	Cool down from 98°C-80°C: 167 minutes
Output per hour	Litres: 31
	Pints: 55
	Cups: 206
Rapid draw off	Litres: 22
	Pints: 39
	Cups: 146
Recovery per minute	Litres: 0.5
	Pints: 0.88
Tap height	220mm from drip tray (tbc)
Inline water filter	Yes
Replaceable water filter	Yes
Water inlet connection fitting	³⁄4″ BSP
Water feed hose length (Supplied) (m)	2
Max Water inlet pressure (bar)	10
Voltage supply	230V 50-60Hz
Electrical Supply 1N~+E current (A)	13
Plug type	UK
Fitted cable length (m)	1.7
None slip feet for safety	Yes
Boil dry thermal cut out	Yes
Country of manufacture	UK
Tariff code	8516101100
WRAS approved	Yes
Warranty	Up to 2 years Parts & Labour