

## Demand more. Choose Foster

# Foster Display Chiller 900mm Open Front Self Service FDC900



#### Temperature



#### Dimensions (mm)

W 900 D 785

H 1435

#### Capacity

115 Litres

### **Unpacked Weight**

#### Features & Benefits

If you want best in class British made self-service display, Foster Display Chillers are for you, giving your customers every opportunity to buy on impulse without losing produce quality. The open fronted range is perfect for the storage and display of pre-packaged products such as drinks, sandwiches, sushi and dairy produce.

- ACT (Anti Condensation Technology) helps glass to remain clear, maximising product display
- Glass end panels over 70% wider than many models in the market, maximising your display window
- Thick toughened glass for enhanced safety across both open and closed fronted models
- Manufactured using superior 304 stainless steel the 'gold standard' in performance finishes meaning quality is assured
- Foster's innovative air curtain protects your merchandise from warmer air entering the display ensuring your food keeps both its taste and texture
- Brilliantly bright LED lighting in top canopy and on every shelf significantly enhances product display
- Innovative design means the controller can be positioned to the front or rear allowing on site flexibility
- There when you need us: Unrivalled 2 year parts and labour warranty as standard for complete peace of mind (UK only)

External Finish				
304 Stainless Steel		Standard		
Internal Finish				
304 Stainless Steel		Standard		
Shelving				
10mm Thick Glass Shelving	Quantity: 3	Standard		
Base Fittings				
Roller Castors		Standard		

Refrigeration				
Forced Air	Standard			
Integral	Standard			
Depth	Please allow an additional			
Note:	80mm to the depth of the			
	product as spacers are			
	required for air circulation			
	(fitted as standard). The unit			
	is designed to operate at M2			
	temperature requirements			
	(EN441 Climate Class 3 25°			
	ambient)			
R404a	Standard			

Electrical Data & Service Information		
	230 Volts	Standard
	50Hz	Standard
	1 Phase	Standard
	Fuse Required (A)	10 amp
ı		

#### Footnotes

• Add 80mm to depth for spacers if product is to be wall-sited (required for air circulation - detachable if not wall-sited)

## Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: 0843 216 8800 Facsimile: 0843 216 4700 Email: sales@foster-uk.com













ISO 14001



Demand more. Choose Foster