



FREESTANDING FRYERS



LD48 fryer

KEY FEATURES

- Two free-standing models availability
- *choose to suit your level of business*
- One-piece, stainless steel plunged hob and pan
- *easy to clean*
- Easy to remove element box
- *stand up to rigorous use*

MODELS and ACCESSORIES

LD46 single pan fryer (8 litre)
LD48 twin pan fryer (2 x 8 litre)

- No accessories

MODEL DIMENSIONS (in mm)

LD46 : 300mm (w) x 630mm (d) x 965mm (h)
LD48 : 600mm (w) x 630mm (d) x 965mm (h)

SPECIFICATION DETAILS

	LD46	LD48
Rating (kW)	6	2 x 6
Supply voltage	400V 2N~	400V 2N~
Current split (amps)	L1: 13, L2: 13	2 x (L1: 13, L2: 13)
Chip output (kg per hour)	20	37
No. of baskets	1	2
Weight (kg)	29	50
Packed weight (kg)	30	52

INSTALLATION NOTES

Adequate ventilation must be provided to supply sufficient fresh air and to allow easy removal of any such products that may present a risk to health.

Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit position. A clearance of 150mm should be observed between appliance and any combustible wall.

