

Product Code: EP700W 10-157 EcoPro G2 600 Litre Upright Glass Door Wine Cabinet



Features & Benefits

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- · All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Glass door cabinet for easy visibility of stored product, operates up to 32 degrees
- Energy efficiency LED lighting for clear display
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

| External Finish | | |
|---|----------|--|
| s/steel ext, 304 s/s door | Standard | |
| 304 S/S back for island sitting | Option | |
| Base Fittings | | |
| Castors 80mm | Standard | |
| Legs 150mm | Option | |
| Electrical, Service & Ecodesign Data | | |
| 230/50/1 | Standard | |
| 220/60/1 Electrical Supply | Option | |

| Internal Finish | |
|-----------------------|----------|
| aluminium | Standard |
| Doors | |
| Glass | Standard |
| Left Hand Hinged Door | Option |
| Product Extras | |
| Helicoil Mains Lead | Option |

| Shelving | |
|-------------------------------|----------|
| Additional S/S Trayslides | Option |
| Additional GN2/1 Shelf | Option |
| Refrigeration | |
| R290 - Energy Efficient | Standard |
| Integral Refrigeration System | Standard |
| Less Condensing Unit | Option |
| Remote Refrigeration System | Option |
| Specification | |
| Dimensions (Width) | 700 |
| Dimensions (Height) | 2080 |
| Dimensions (Depth) | 820 |
| Weight (Unpacked, kg) | 121 |
| Weight (Packed, kg) | 132.6 |
| Gross Volume | 600 |

64.9

Noise Dba @ 1M

Footnotes

Fuse Required

• Hydrocarbon option not available on glass door models

13

- 32° C ambient on glass door refrigerator model
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet











