



AN501BTCR/09

### SPECIFICATION

|                               |  |
|-------------------------------|--|
| <b>Exterior</b>               | AISI 304 Stainless Steel with Double Glazed Door |
| <b>Interior</b>               | AISI 304 Stainless Steel                         |
| <b>Insulation</b>             | CFC Free Polyurethane                            |
| <b>Integral door handles</b>  | Yes  |
| <b>Shelves</b>                | 3  |
| <b>Doors</b>                  | 1  |
| <b>Containers</b>             | N/A  |
| <b>Volume</b>                 | 470ltr   |
| <b>Legs</b>                   | 4 Adjustable                                     |
| <b>Condensate evaporation</b> | Forced Air                                       |
| <b>Compressor Hp</b>          | 5/8  |
| <b>Condenser</b>              | Ventilated                                       |
| <b>Defrost</b>                | Auto   |
| <b>Electronic controller</b>  | DIXCEL XW60L or CAREL PJ1FS                      |
| <b>Temperature range</b>      | -18°C  |
| <b>Ambient range</b>          | To +32°C   |
| <b>Refrigerant</b>            | R404a  |
| <b>Load when running</b>      | 1035w  |
| <b>Supply</b>                 | 13 amp   |
| <b>External Height</b>        | 2030mm   |
| <b>Width</b>                  | 687mm  |
| <b>Depth</b>                  | 695mm  |

