



Product Code: MBCFT75W

Modular Blast Chiller with 900mm door width c/w 25mm floor and integral ramp



Features & Benefits

- MBCT models are supplied floorless for blast chilling application only
- Chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Freezing capacity from 70° to -18°C in less than 240 minutes within specifications
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status.
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Operator-friendly fans cut-out whenever door is opened
- HACCP software is available as an option in 3 formats for data retrieval and management

External Finish	Internal Finish	Shelving
White lam ext and door / white control panel Standard	White lam Standard	Additional S/S Trayslides Standard
White lam ext, 304 s/s door and white control panel Option	304 s/s Option	Trolley - Gastronorm - 1/1 (Not Supplied) Option
304 s/s ext Option	Refrigeration	Trolley - Gastronorm - 2/1 (Not Supplied) Option
Doors	R404a - Industry Standard Standard	Trolley Capacity - 890x1040x1890 Standard
Solid Standard	Less Condensing Unit Standard	Electrical, Service & Ecodesign Data
Left Hand Hinged Door Option	Remote Refrigeration System Standard	230/50/1 Standard
Product Extras	Specification	
Hold Facility Option	Dimensions (Width) 1550	
	Dimensions (Height) 2350	
	Dimensions (Depth) 1330	
	Weight (Unpacked, kg) 790	
	Weight (Packed, kg) 790	
	Chilling Capacity (Kgs) 75	
	Gross Volume 75	
	RS485 connection for HACCP data logging Option	
	Noise DbA @ 1M TBC	

Footnotes

- MBC models are supplied floorless for blast chilling application only.
- Control panel sprayed white
- Capacity 75kg. Chilling capacity 70oC to 3oC in less than 90 minutes within specifications. Entry temperature or up to 90oC for chilling.
- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15oC e.g. Prep rooms
- Condensing Unit: All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral).



Energy



Quality



Value



Design



Hygiene



After Care