

Vacuum packing machine SU-520 230/50-60/1

TECHNICAL SPECIFICATIONS

Pump capacity: 20 m³/h
 Bar length: 420 mm
 Total loading: 750 W
 Vacuum pressure (maximum): 2 mbar

Electrical supply: 230 V / 50-60 Hz / 1 ~ (5.5 A)

Internal dimensions

·Width: 560 mm
 ·Depth: 430 mm
 ·Height: 183 mm

External dimensions (WxDxH)

·Width: 625 mm
 ·Depth: 537 mm
 ·Height: 513 mm

Net weight: 80 Kg
 Noise level (1m.): 75 dB(A)
 Background noise: 32 dB(A)



DEFAULT EQUIPMENT

- BUSCH pump.
- Sensor Controls.
- 25 programmable settings.
- Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- Soft air function.
- Clear methacrylate lid.
- "PAUSE" function.
- Liquid detection system.

OPTIONAL EQUIPMENT

- Vacuum packing pouches
- Vac-Norm external vacuum kit, containers and accessories
- Bag cutting kit
- Support for liquids
- Additional filling plates



Vacuum packing machine SU-520 230/50-60/1

TABLETOP MODEL. 20M³/H. 420+420 MM.

**Two sealing bars (420+420 mm.)
20 m³/h Busch vacuum pump.
Vacuum controlled by sensor.**

- Powered by Busch.
- Vacuum controlled by sensor.
- Vacuum PLUS.
- LCD colour screen: all information at a glance.
- Backlit touch keyboard.
- Programmable: 25-programme memory. Blocking option.
- "Pause" button.
- Phased vacuum programme.
- Detection of the evaporation of liquids.
- Double seal.
- Cordless sealing bar.
- Progressive decompression.
- Vac-Norm ready with Automatic decompression.
- Stainless steel body and chamber. Long-shaped chamber.
- Damped transparent lid of high durability polycarbonate.
- Dry-oil programme for drying the pump.
- Working hours counter for oil changes.
- Safety system with protection against vacuum failure.