



Demand more. Choose Foster

# MBCT250 Modular Blast Chiller

## MBCT250



### Temperature

 Blast Chiller 70/3 °C

### Dimensions (mm)

|        |                                                                                     |                                                                                     |
|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|        | W 1350                                                                              | D 2330                                                                              |
| H 2350 |  |  |

### Capacity

undefined Litres  
250 Chilling (Kg)

### Unpacked Weight

790 KG

### Features & Benefits

Our Modular Blast Chill/Freeze range is designed to cope with the multi-purpose requirement of the foodservice industry, and enables you to take control of the Cook-Chill Process

- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status.
- Capable of blast chilling from +70°C to +3°C in 90 minutes
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Operator-friendly fans cut-out whenever door is opened
- HACCP software is available as an option in 3 formats for data retrieval and management

| External Finish      |              | Doors                         |          | Electrical Data & Service Information |          |
|----------------------|--------------|-------------------------------|----------|---------------------------------------|----------|
| 304 Stainless Steel  | Option       | Solid Full                    | Standard | 400 Volts                             | Standard |
| Stainless Steel Door | Option       | Hinged - Right Hand           | Standard | 50Hz                                  | Standard |
| Foodsafe             | Standard     | Hinged - Left Hand            | Option   | 3 Phase                               | Standard |
|                      |              | Pass Through                  | Option   | Running Watts                         | 1707     |
| Internal Finish      |              | Refrigeration                 |          | Running Amps                          | 1.3      |
| 304 Stainless Steel  | Option       | Forced Air                    | Standard | Thermal Heat Rejection (W)            | 3,387    |
| Foodsafe             | Standard     | Remote - less condensing unit | Standard | Noise (dBa @ 1m)                      | TBC      |
|                      |              | R404a                         | Standard | Fuse Required (A)                     | 0 amp    |
| Shelving             |              |                               |          | Product Extras                        |          |
| Trolley Capacity     | Not Supplied |                               |          | Door Pull Handle                      | Standard |
| -                    |              |                               |          | Hold Facility                         | Option   |
| 690x1040x1890        |              |                               |          | Temperature Probe                     | Option   |
|                      |              |                               |          | Hardwired Logging System Interface    | Option   |
|                      |              |                               |          | Food Probe                            | Option   |
|                      |              |                               |          | Anti Condensation on Control Panel    | Option   |

## Footnotes

- MBC models are supplied floorless for blast chilling application only. MBCF models are supplied complete with 25mm floor and are suitable for occasional blast freezing and non-ground floor sites
- Control panel sprayed white
- Capacity 250kg. Chilling capacity 70oC to 3oC in less than 90 minutes within specifications. Entry temperature or up to 90oC for chilling.
- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15oC e.g. Prep rooms
- Condensing Unit: All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral).

## Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: [sales@foster-uk.com](mailto:sales@foster-uk.com)

**FOSTER  
GREEN  
PROCUREMENT**



**Demand more. Choose Foster**

